



FEMALE

A04	A05	A08	D04	B05

NOTE:

<b>MATERIAL</b>	
M12 INSULATOR	PA66, UL94V-0, BLACK
CONTACT	GOLD FLASH PLATED BRASS
NUT & SHELL	NICKEL PLATED BRASS
<b>ELECTRICAL</b>	
RATED CURRENT	2A(8P) / 4A(4/5P)
VOLTAGE	30V(8P) / 60V(5P) / 250V(4P)
INSULATOR RESISTANCE	100 MOhms MIN.
CONTACT RESISTANCE	10 mOhms MAX.
MATING CYCLES	100 CYCLES MIN
<b>ENVIRONMENT</b>	
OPERATION TEMPERATURE	-40°C TO +85°C
IP RATING	IP67
RECOMMENDED TORQUE	0.4Nm TO 0.8Nm

858FYYY-203RCS1

SERIES \_\_\_\_\_

858F = M12 FIELD INSTALLABLE

CONTACT ARRANGEMENT \_\_\_\_\_

A04 = 4P A-CODE

A05 = 5P A-CODE

A08 = 8P A-CODE

D04 = 4P D-CODE

B05 = 5P B-CODE

GENDER \_\_\_\_\_

2 = FEMALE

CABLE OD \_\_\_\_\_

C = 4mm-8mm OD

CONTACT PLATING \_\_\_\_\_

1 = GOLD FLASH

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

02/04/2022

NorComp

SCALE: NTS

SHEET 1 OF 1

REV 0

DWG NO.

858FYYY-203RCS1