

TOLERANCE UNLESS OTHERWISE SPECIFIED .X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER

(1)



ORIGINAL



14.48 11.94 0 0 **(** ٦ ٦ ٦ $\widehat{}$

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING: 50Ω (IMPEDANCE) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT


SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

1000V AC rms

5000MΩ min.

-55°C ~ 125°C



ſ	COMBINATION D-SUB			SW REFERENCE NO.: 630 COMBO ASSEMBLY					
				DRAWN: C.B			DATE: JAN. 01/2019		
				CHECKED:		DATE:			
YOUR	EDAC	EDAC INC TORONTO, ONTARIO CANADA 9 QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	(IN C.A.D. 1	:1)	SHEET 1 OF	2	
				DRAWING NUMBER: 630-24W7			240-5ND	ISSUE	
	YOUR CONNECTION TO QUALITY & S			PART NU	MBER:	630-24W7	240-5ND	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

