

Data sheet | Item number: 706-5030/203-100

System cable; for Gefanuc 9030; 5 digital outputs for higher voltages;

Length: 1 m; Conductor cross-section: 0.34 mm<sup>2</sup>

[www.wago.com/706-5030/203-100](http://www.wago.com/706-5030/203-100)



Color coding acc. to DIN VDE 47 100 Cable 1; Channel 0-3		WAGO 231 series (JA)		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		1	0.0	2	HA1
Brown		2	0.1	4	OA1
Green		3	0.2	6	HA2
Yellow		4	0.3	8	OA2
Grey		5	0.4	10	HA3
Pink		6	0.5	12	OA3
Blue		7	0.6	14	HA4
Red		8	0.7	16	OA4
Black		9	nc	nc	nc
Violet		10	nc	nc	nc

  

Color coding acc. to DIN VDE 47 100 Cable 2; Channel 4		WAGO 231 series (JB)		PLC connector	
		Pin number	Wiring	Pin number	Signal
White		11	1.0	18	HA5
Brown		12	1.1	20	OA5
Green		13	nc	nc	nc
Yellow		14	nc	nc	nc
Grey		15	nc	nc	nc
Pink		16	nc	nc	nc
Blue		17	nc	nc	nc
Red		18	nc	nc	nc
Black		19	nc	nc	nc
Violet		20	nc	nc	nc

Data  
Notes

Note

If less than 3 channels are used simultaneously, the maximum current per conductor is 2 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L. If more than 3 channels are used simultaneously, the maximum current per conductor is 0.75 A and up to 5 A (30°C ambient temperature) or 3.5 A (50°C ambient temperature) at pins N/L.

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



## Electrical data

Inputs/outputs	5 digital outputs; for higher voltages
Operating voltage	≤ AC/DC 250 V
Current per wire (max.)	0.75 A

## Compatibility

### GE Fanuc

GE Fanuc 9030	IC693 MDL390
---------------	--------------

## Connection data

Cable type	LiYY
Color code	per DIN VDE 47100

## Connection 1

Connector	WAGO 231 Series
Pole number 1	10
Connection type 1	System
Wire cross-section	0.34 mm <sup>2</sup>

## Connection 2

Connector 2	WAGO 231 Series
Pole number 2	10
Connection type 2	System

## Connection 3

Connector 3	GeFanuc IC 693 ACC 311
Pole number 3	20
Connection type 3	System

## Physical data

Cable length	1 m
--------------	-----

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



## Material Data

Weight	362 g
--------	-------

## Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

## Commercial data

ETIM 8.0	EC000237
ETIM 7.0	EC000237
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	FR
GTIN	4055143986212
Customs tariff number	85444290900

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Downloads

### Documentation

#### System Description

WAGO System Wiring, Selection Guide This guide will help you select the appropriate interface modules and system cables for the controller you are using.	pdf 545.9 kB	Download
--	-----------------	----------

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 706-5030/203-100 System cable; for Gefanuc 9030; 5 digital outputs for higher voltages; Length: 1 m; Conductor cross-section: 0.34 mm <sup>2</sup>	URL	Download
---	-----	----------

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.