



Illuminated pushbutton, 30 mm, round, Metal, matte, clear, front ring for flush installation, latching, Push-to-release mechanism, with laser labeling, upper case

|  |                                     |
|--|-------------------------------------|
| product brand name                                 | SIRIUS ACT                          |
| product designation                                | Illuminated pushbuttons             |
| design of the product                              | Actuating/signaling element         |
| product type designation                           | 3SU1                                |
| product line                                       | Metal, matt, flat, 30 mm            |
| <b>Enclosure</b>                                   |                                     |
| number of command points                           | 1                                   |
| <b>Actuator</b>                                    |                                     |
| design of the actuating element                    | Flat button                         |
| principle of operation of the actuating element    | latching                            |
| product extension optional                         |                                     |
| • light source                                     | Yes                                 |
| • contact module                                   | Yes                                 |
| color of the actuating element                     | clear                               |
| material of the actuating element                  | plastic                             |
| shape of the actuating element                     | round                               |
| outer diameter of the actuating element            | 38 mm                               |
| marking of the actuating element                   | Any inscription, text in upper case |
| type of unlocking device                           | push-to-unlatch mechanism           |
| <b>Front ring</b>                                  |                                     |
| product component front ring                       | Yes                                 |
| design of the front ring                           | Flat                                |
| material of the front ring                         | Metal, matt                         |
| color of the front ring                            | sand gray                           |
| <b>General technical data</b>                      |                                     |
| protection class IP                                | IP66, IP67, IP69(IP69K)             |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13          |
| shock resistance                                   |                                     |
| • acc. to IEC 60068-2-27                           | Sinusoidal half-wave 50g / 11 ms    |
| • for railway applications acc. to DIN EN 61373    | Category 1, Class B                 |
| vibration resistance                               |                                     |
| • acc. to IEC 60068-2-6                            | 10 ... 500 Hz: 5g                   |
| • for railway applications acc. to DIN EN 61373    | Category 1, Class B                 |
| operating frequency maximum                        | 1 800 1/h                           |
| mechanical service life (switching cycles) typical | 500 000                             |
| reference code acc. to IEC 81346-2                 | S                                   |
| <b>Ambient conditions</b>                          |                                     |

- ambient temperature during operation
- ambient temperature during storage

-25 ... +70 °C

-40 ... +80 °C

environmental category during operation acc. to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)

#### Installation/ mounting/ dimensions

|   |         |
|---|---------|
| height                                      | 38 mm   |
| width                                       | 38 mm   |
| shape of the installation opening           | round   |
| mounting diameter                           | 30.5 mm |
| positive tolerance of installation diameter | 0.5 mm  |
| mounting height                             | 4.2 mm  |
| installation width                          | 38 mm   |
| installation depth                          | 31.1 mm |

#### Certificates/ approvals

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1061-0JA70-0AA0-Z Y11>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1061-0JA70-0AA0-Z Y11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1061-0JA70-0AA0-Z Y11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1061-0JA70-0AA0-Z Y11&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1061-0JA70-0AA0-Z Y11&lang=en)

last modified:

12/21/2020 