# DT16-18SE-K004 ✓ ACTIVE

#### DEUTSCH | DEUTSCH DT

TE Internal #: DT16-18SE-K004

Housing for Female Terminals, Wire-to-Wire, 18 Position, .184 in [4.67 mm] Centerline, Sealable, Black, Wire & Cable, Power &

Signal, DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [ .063 in ]

Connector System: Wire-to-Wire

Number of Positions: 18

Centerline (Pitch): 4.67 mm [.184 in]

#### **Features**

#### **Product Type Features**

Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Contact Retainer
Connector & Contact Terminates To	Wire & Cable

### **Configuration Features**

Connector Modification	Enhanced Seal Retention, End Cap
Connector Seal Code	E Seal
Number of Positions	18
Number of Rows	3

#### **Electrical Characteristics**

Operating Voltage	250 VAC	



Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	E
Contact Features	
Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	4.67 mm[.184 in]
Dimensions	
Connector Height	43.82 mm[1.725 in]
Product Width	20.98 mm[.826 in]
Product Length	35.38 mm[1.393 in]
Row-to-Row Spacing	4.83 mm[.19 in]
Accepts Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	Not Tested



UL Flammability Rating	Not tested
Packaging Features	
Packaging Quantity	500
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### Compatible Parts












### Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers (107)



Automotive Connector Locks & Position Assurance(74)



Automotive Housings(618)



Automotive Seals & Cavity Plugs(5)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(16)



PCB Headers & Receptacles(102)

## Customers Also Bought



TE Part #HDP26-24-21PN-L017
DEUTSCH HDP20 Housings



TE Part #W2SA-P012 WEDGE LOCK, 2P, PLG, GRY, SL RET, DT, A



TE Part #DT16-18SA-K004 PLG, 18P, BLK, E, A





PLG, 18P, BLK, E, C



PLG, 18P, BLK, E, B





#### **Documents**

**Product Drawings** 

PLG, 18P, BLK, E, E

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SE-K004\_G.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SE-K004\_G.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT16-18SE-K004\_G.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English