

TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE
 DO NOT MAKE MANUAL REVISIONS TO MASTER.

 .X
 ±0.25










.XX ±0.13 .XXX ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED



SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT	Ć
POWER/CO-AX CONTACT RATING: (IF PRESENT)	75Ω (IMPEDANCE)	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
	5510 40510	

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.

1000V AC rms



ſ	SW REFERENCE NO.: 629 COMBO ASS					OMBO ASSEME	ιLY	
		COMBINATION	D-SUB	DRAWN: C.B		DATE: JAN.	01/20	19
				CHECKED:		DATE:		
		EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SE DRAWINGS AND SPECIFICATIONS THE PROPERTY OF EDAC INC.,AND SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2				
		TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-13W		/3640-7N5		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER:	629-13W3	629-13W3640-7N5		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

