

## C 091 D Characteristics

| General Characteristics                         | Standard                          | Characteristics  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
|---|-----------------------------------|--|----------------|---------------------|-------------------|---------------------|-------------------|---------------------|-----------|---------------------|---|---------------------|
| Number of contacts                              |                                   | 3  | 4              | 5                   | 5 Stereo          | 6                   | 7                 | 7                   | 8         | 12                  | 14  |                     |
| View on termination side of male contact insert |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Contact arrangement                             | DIN EN 61076-2-106                | 03-a<br>✓  | 04-a<br>✓      | 05-a<br>✓           | 05-b<br>✓         | 06-a<br>✓           | 07-a<br>✓         | 07-b<br>✓           | 08-a<br>✓ | 12-a<br>✓           | 14-a<br>✓   |                     |
| Contact arrangement                             | IEC 60130-9 <sup>1)</sup>         | ✓  | ✓              |                     | ✓                 | ✓                   |                   | ✓                   | ✓         |                     |   |                     |
| Electrical Characteristics                      |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Rated voltage <sup>2)</sup>                     | IEC 60664-1                       | 300 V ≈<br>(100 V ≈)   |                | 300 V ≈<br>(63 V ≈) |                   | 100 V ≈<br>(32 V ≈) |                   | 300 V ≈<br>(63 V ≈) |           | 100 V ≈<br>(32 V ≈) |   | 150 V ≈<br>(32 V ≈) |
| Rated voltage                                   | UL 1977                           | 250 V  |                |                     |                   |                     |                   |                     |           |                     | 60 V  |                     |
| Rated impulse withstand voltage <sup>2)</sup>   | IEC 60664-1                       | 1500 V<br>(840 V)  |                |                     | 1200 V<br>(500 V) |                     | 1500 V<br>(840 V) |                     |           | 1200 V<br>(500 V)   |   |                     |
| Pollution degree <sup>2)</sup>                  | IEC 60664-1                       | 1 (3 <sup>3)</sup> )   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Installation category                           | IEC 60664-1                       | I  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Insulation group                                | IEC 60664-1                       | II, 400 ≤ CTI < 600  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Current rating                                  | IEC 60512-5-2<br>UL 1977          | 5 A / + 40 °C / + 104 °F<br>please refer also to current derating curves page 59   |                |                     |                   |                     |                   |                     |           |                     | 3 A / + 40 °C /<br>+ 104 °F   |                     |
| Insulation resistance                           | IEC 60512-3-1                     | > 10 <sup>10</sup> Ω <sup>4)</sup>   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Contact resistance                              | IEC 60512-2-1                     | < 5 m Ω  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Climatic Characteristics                        |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Climatic category                               | IEC 60668-1                       | 40 / 100 / 56  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Temperature range                               | IEC 60668-1                       | - 40 °C ... + 100 °C / - 40 °F ... + 212 °F  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Salt Spray Resistance                           | DIN IEC 60068-2-11, Test Ka       | 720h   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Mechanical Characteristics                      |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| IP-degree                                       | IEC 60529                         | IP 67 and IP 65 (in mated condition)   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Insertion and withdrawal forces                 | IEC 60512-13-2                    | 25 N<br>90.oz  | 30 N<br>110.oz | 35 N<br>125.oz      | 50 N<br>180.oz    | 55 N<br>200.oz      | 60 N<br>220.oz    | 50 N<br>180.oz      |           |                     |   |                     |
| Mechanical operation                            | IEC 60512-9-1                     | Silver ≥ 500 mating cycles<br>Gold ≥ 1000 mating cycles  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Materials                                       |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Housing material                                |                                   | coupling ring brass, strain relief, die cast, nickel plated  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Dielectric material                             |                                   | thermoplastic  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Contact plating                                 |                                   | silver plated / gold plated <sup>5)</sup>  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Further Characteristics                         |                                   |  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Termination technique                           |                                   | solder, crimp  |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Wire gauge                                      |                                   | solder: ≤ 0,5 mm <sup>2</sup> / 20 AWG<br>crimp: 2 - 6 pol (excluding 5S): 0,09 - 1,00 mm <sup>2</sup> / 28 - 18 AWG<br>crimp: 5S, 7, 7S and 8-pol.: 0,09 - 0,75 mm <sup>2</sup> / 28 - 20 AWG |                |                     |                   |                     |                   |                     |           |                     | solder: ≤ 0,25 mm <sup>2</sup> /<br>24 AWG<br>crimp: 0,09-0,25 mm <sup>2</sup> /<br>28 - 24 AWG |                     |
| Flammability                                    |                                   | UL 94 V0   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| Locking system                                  | IEC 60130-9<br>DIN EN 61076-2-106 | metal screw coupling; tightening torque 0,7 Nm   |                |                     |                   |                     |                   |                     |           |                     |   |                     |
| UL  | UL 1977                           | Conditions of acceptability  |                |                     |                   |                     |                   |                     |           |                     |   |                     |

**Caution:** Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.

<sup>1)</sup> Edition 2000-05

<sup>2)</sup> values in brackets are according to DIN EN 61076-2-106

<sup>3)</sup> designed acc. pollution degree 2; can be used under pollution degree 3 when the rules of IEC 60644-1 are fulfilled

<sup>4)</sup> under operating conditions >10<sup>8</sup> Ω

<sup>5)</sup> Remark for gold plated contacts: In order to avoid brittle inter-metallic connections, gold-plated terminals have to be tin-plated in the solder area.

IEC 60 664 ≙ DIN VDE 0110 ; IEC 60 512-x ≙ DIN EN 60 512-x; IEC 60 130-9 ≙ DIN EN 60 130-9; IEC 61076-2-106 ≙ DIN EN 61076-2-106