



KEY CODE
A126

NOTES:

1. ALL DIMENSIONS IN MM[INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 4A @ 125VAC, 2A @ 250VAC
5. CONTACT RESISTANCE: 20 milli-OHMS MAX.
6. DIELECTRIC STRENGTH: 1,500 VAC-1Minute
7. MATERIALS:
HOUSING: NICKEL PLATED ZINC ALLOY WITH NICKEL FACING
CYLINDER: NICKEL PLATED ZINC ALLOY
TERMINAL AND CONTACTS: GOLD PLATED COPPER ALLOY
KEYS (2): BRASS
8. 2002/95/EC (ROHS) COMPLIANT



CONNECTED TERMINAL #			
POS. 1	POS. 3	POS. 4	POS. 5
6-7	7-1	1-2	2-3



LEGEND

- = Detent positions
- = Key pull possible in these positions



TITLE KO130Z1A126

A	20568	Release For Production	4/25/12	rc
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
1:1	4/25/2012	rc	K200298	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED