


	(IF PRESENT)	40A (CORREN
	SIGNAL CONTACT CURRENT RATING:	5A PER CONT/
	SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
00	INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.
	WITHSTANDING VOLTAGE:	1000V AC rms



(1)

			SW REFERENCE NO.: 630 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
EDAC INC TORONTO, ONTAF CANADA	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-17W5250-4TA		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-17W	5250-4TA	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

