



- NOTES:
- MATERIALS:
INSULATOR IS GLASS FILLED LCP (LIQUID CRYSTAL POLYMER), U.L. 94 V-0, COLOR: BLACK;
TERMINALS ARE A PHOSPHOR BRONZE ALLOY, .012" THICK.
 - TERMINAL PLATING:
30 MICROINCHES/(0.762 MICROMETERS) MINIMUM GOLD IN SELECT AREA;
100 MICROINCHES/(2.54 MICROMETERS) MINIMUM TIN IN SELECTE AREA;
OVER NICKEL UNDERPLATE OVERALL.
 - PARTS USED IN CONJUNCTION WITH MOLEX PRODUCT SPECIFICATION #PS-71719-9999.
 - PACKAGING PER MOLEX SPECIFICATION #PK-70873-0252.
 - PARTS CONFORM TO MOLEX APPLICATION SPECIFICATION #AS-71715-9999.

NOTE FOR LEAD FREE CONVERSION:
THE PRIMARY SHIPPING CARTON WILL BE
LABELED "COMPLIANT TO ROHS DIRECTIVE
2002/95/EC AND ELV ANNEX II OF
DIRECTIVE 2000/53/EC". CARTONS
WITHOUT THIS LABEL MAY CONTAIN
PRODUCT WITH LEAD.

L.T.R.		REVISIONS		L.T.R.		REVISIONS		DIMENSIONS SHOWN <input checked="" type="checkbox"/> INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2° 3 PLACE ± .010 --- 2 PLACE ± --- ± --- 1 PLACE --- ± --- DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DRWG. BY: GLT APP'D. BY: CWF CHK'D. BY: GLT SCALE: 5:1		MFG. SH. REV. TITLE: .050" PITCH LFH, 50 CKT. MALE INSERT-MOLDED CONTACT STRIP, SALES DETAIL MOLEX INCORPORATED LITSE, ILL. 60532 SHEET NO. 1 OF 1 DATE 09/06/95 U.S.A. FILE NAME: S7171503.DGN THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.	
--------	--	-----------	--	--------	--	-----------	--	---	--	--	--