



Compact Safety Padlocks

TDS No. LOTO9
Effective Date: 08/12/2019

Description:

<p>Design</p> <ul style="list-style-type: none"> • Compact, lightweight, and enhanced impact resistance. • Superior corrosion and chemical resistance • Non-conductive, spark resistant lock body • Insulated key chamber protects workers from shock when the key is inserted • Key won't release until the padlock shackle is securely closed 																																					
<p>Material</p> <ul style="list-style-type: none"> • Lock body made from Polyamide Nylon 66 • Color: Lock Body • Black • Green • Blue • Viole • Red • Whit • Yello • Brow • Orange • Grey • Shackle made from Aluminum • Color: Shackle – Black • UL Rating - UL 94 – HB (Plastic Components Only) 	<table border="1"> <thead> <tr> <th>Chemical</th> <th>°C</th> <th>Chemical</th> <th>°C</th> </tr> </thead> <tbody> <tr> <td>Acetone</td> <td>15 – 60</td> <td>Nickel salt solns. (chloride, sulfate)</td> <td>15 – 30</td> </tr> <tr> <td>Ammonia soln.</td> <td>15 – 30</td> <td>Petroleum</td> <td>15 – 30</td> </tr> <tr> <td>Ammonia soln.</td> <td>48</td> <td>Silicone oils</td> <td>< 80</td> </tr> <tr> <td>Fuel, engine: Gasoline (Leaded & Unleaded)</td> <td>48</td> <td>Toluene</td> <td>15 – 30</td> </tr> <tr> <td>Fuel, Diesel</td> <td>85</td> <td>Water (including seawater)</td> <td>15 – 30</td> </tr> <tr> <td>Heptane</td> <td>15 – 30</td> <td>Water (including seawater), chlorinated (<0,5 mg/l)</td> <td>80</td> </tr> <tr> <td>Lubrication oil: gear oil</td> <td>< 130</td> <td>Zinc chloride</td> <td>15 – 30</td> </tr> <tr> <td>Lubricating oil: HD engine oils, hydraulic oils, transformer oils</td> <td>< 130</td> <td></td> <td></td> </tr> </tbody> </table>	Chemical	°C	Chemical	°C	Acetone	15 – 60	Nickel salt solns. (chloride, sulfate)	15 – 30	Ammonia soln.	15 – 30	Petroleum	15 – 30	Ammonia soln.	48	Silicone oils	< 80	Fuel, engine: Gasoline (Leaded & Unleaded)	48	Toluene	15 – 30	Fuel, Diesel	85	Water (including seawater)	15 – 30	Heptane	15 – 30	Water (including seawater), chlorinated (<0,5 mg/l)	80	Lubrication oil: gear oil	< 130	Zinc chloride	15 – 30	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 130		
Chemical	°C	Chemical	°C																																		
Acetone	15 – 60	Nickel salt solns. (chloride, sulfate)	15 – 30																																		
Ammonia soln.	15 – 30	Petroleum	15 – 30																																		
Ammonia soln.	48	Silicone oils	< 80																																		
Fuel, engine: Gasoline (Leaded & Unleaded)	48	Toluene	15 – 30																																		
Fuel, Diesel	85	Water (including seawater)	15 – 30																																		
Heptane	15 – 30	Water (including seawater), chlorinated (<0,5 mg/l)	80																																		
Lubrication oil: gear oil	< 130	Zinc chloride	15 – 30																																		
Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 130																																				
<p>Temperature Range</p> <p>Service Temperature: -20° to 120°C (-0° to 250°F)</p>																																					
<p>Chemical Resistance</p> <p>All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.</p>																																					
<p>Dimensions</p> <table border="1"> <tbody> <tr> <td>"A"</td> <td>–</td> <td>1.26" [32mm]</td> </tr> <tr> <td>"B"</td> <td>–</td> <td>1.38" [35mm]</td> </tr> <tr> <td>"C"</td> <td>–</td> <td>0.63" [16mm]</td> </tr> <tr> <td rowspan="4">"D"</td> <td>–</td> <td>1.00" [25.5mm]</td> </tr> <tr> <td>–</td> <td>1.50" [38mm]</td> </tr> <tr> <td>–</td> <td>2.00" [50mm]</td> </tr> <tr> <td>–</td> <td>3.00" [25.5mm]</td> </tr> <tr> <td>"ØE"</td> <td>–</td> <td>Ø0.19" [4.74]</td> </tr> </tbody> </table>	"A"	–	1.26" [32mm]	"B"	–	1.38" [35mm]	"C"	–	0.63" [16mm]	"D"	–	1.00" [25.5mm]	–	1.50" [38mm]	–	2.00" [50mm]	–	3.00" [25.5mm]	"ØE"	–	Ø0.19" [4.74]																
"A"	–	1.26" [32mm]																																			
"B"	–	1.38" [35mm]																																			
"C"	–	0.63" [16mm]																																			
"D"	–	1.00" [25.5mm]																																			
	–	1.50" [38mm]																																			
	–	2.00" [50mm]																																			
	–	3.00" [25.5mm]																																			
"ØE"	–	Ø0.19" [4.74]																																			

Catalog Numbers

Brady - North America

www.bradyid.com

Brady - Europe

www.en.bradyeurope.com

Brady - Asia/Pacific

www.brady.com.cn

1 Padlock -Keyed Different	6 Padlock -Keyed Different	3 Padlocks -Keyed Alike	6 Padlocks -Keyed Alike
143150	118926	118953	118954
143152	118927	118955	118956
143154	118928	118957	118958
143156	118929	118959	118960
143158	118930	118961	118962
143160	118931	118963	118964
143162	118932	118965	118966
142164	118933	118967	118968
142166	118934	118969	118970

Details:

MSDS Information

1. HAZARDS IDENTIFICATION

This product is NOT DANGEROUS and contains no hazardous ingredients

2. FIRST AID MEASURES/HEALTH INFORMATION PROTECTION

Eye Contact:	Not applicable, product is inert
Ingestion:	Not applicable, first aid is not normally required.
Inhalation:	Not applicable
Skin Contact:	Not applicable, product is inert, except if product is melted use gloves. For hot melted product, immerse in or flush affected area with water to dissipate heat, then obtain medical attention.
Exposure Limits:	None
Threshold Limits	None
Personal Protection:	None (ambient conditions)
NPCA-HMIS Rating:	Health: 0; Flammability: 1; Reactivity: 0
NFPA-704 Rating:	Health: 0; Flammability: 1; Reactivity: 0

3. FIRE-FIGHTING MEASURES

<ul style="list-style-type: none">Be cautious of hot melted NylonIsolate product from fireExtinguish fire with water spray	<ul style="list-style-type: none">Use water spray to cool fire, exposed surfaces, and to protect personnelRespiratory and eye protection is required for fire fighting personnelDecomposition products under fire conditions: Oxygen-lean conditions may cause monoxide and irritating smoke
--	--

4. ACCIDENTAL RELEASE MEASURES

Land	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations
Water	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.

5. HANDLING AND STORAGE

5.1 Handling	5.2 Storage
No precautions noted-see local regulation if needed	Storage pressure: Atmospheric
	Storage temperature: Ambient, no direct sunlight

6. EXPOSURE CONTROLS/PERSONAL PROTECTION

6.1 Exposure limit values None	6.2 Exposure Controls
	6.2.1 Occupational Exposure Controls
	6.2.1.1 Respiratory Protection: Not applicable
	6.2.1.2 Hand Protection: Not applicable
	6.2.1.3 Eye Protection: Not applicable
	6.2.1.4 Skin Protection: Not applicable
	6.2.2 Environmental Exposure Controls: No data available

7. PHYSICAL AND CHEMICAL PROPERTIES

General Information	
Other Information	

8. STABILITY AND REACTIVITY

8.1 Conditions to Avoid
Higher Temperatures and direct sunlight (chemical resistance is excellent)
Highly stable, but temperatures over 480 F may cause degradation
8.2 Materials to Avoid
No data available
8.3 Hazardous Decomposition Products
Under fire and oxygen-lean conditions may cause monoxide and irritating smoke

9. ECOLOGICAL INFORMATION

9.1 Ecotoxicity	No data available
9.2 Mobility	No data available
9.3 Persistence and Degradability	No data available
9.4 Bioaccumulative Potential	No data available
9.5 Other Adverse Effects	No data available

10. DISPOSAL CONSIDERATIONS

None of the materials in this product are Recyclable, dispose of all materials in accordance with an applicable federal, state, and local law.
--

11. TRANSPORT INFORMATION

No data available

12. REGULATORY INFORMATION

This product has been tested and validated to the Regulatory Requirements listed below.	
• OSHA 29 CFR 1910.147 ©(4)(ii)(A)(1)(c) (5)(ii)(C)(1)	• ANSI standard Z244

13. OTHER INFORMATION

No data available

Trademarks:

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2019 Brady Worldwide, Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

Brady North America | 6555 West Good Hope Road | Milwaukee, Wisconsin 53223 | USA | Tel: 414-358-6600 | Fax: 414-228-5770