



Aerosusa.com
service@aerosusa.com
855.393.9905

RQB90-M



Plastic connector, quick-type, bend 90°, metric outer thread, integrated snap-in sleeve with sealing, high density

Material: PA plastics

Temperature:

-40°C ... +120°C

-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Color: Grey, Black

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest outer dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

Note:

Lock-nuts and sealing washers sold separately. See below for corresponding accessories.

CERTIFICATIONS



"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Aerosusa.com
service@aerosusa.com
855.393.9905

Technical Data Sheet

Product #	Trade Size	AD	Thread	I (in)	B (in)	C (in)	E (in)	F (in)	WS (in)	Ib/100	Color	PU
5103.010.212	1/4"	10	M12 x 1.5	0.26	0.67	0.39	2.24	1.54	0.71	1.7637	Black	50 PC
5103.013.216	5/16"	13	M16 x 1.5	0.33	0.79	0.47	2.32	1.59	0.83	2.2046	Black	50 PC
5103.015.220	3/8"	15.8	M20 x 1.5	0.39	0.91	0.47	2.44	1.77	0.94	3.3069	Black	50 PC
5103.021.220	1/2"	21.2	M20 x 1.5	0.51	1.16	0.47	2.87	1.89	1.02	4.4092	Black	50 PC
5103.021.225	1/2"	21.2	M25 x 1.5	0.57	1.16	0.51	2.87	1.89	1.02	5.0706	Black	50 PC
5103.028.225	3/4"	28.5	M25 x 1.5	0.67	1.46	0.51	3.54	2.52	1.26	7.2752	Black	25 PC
5103.028.232	3/4"	28.5	M32 x 1.5	0.79	1.46	0.55	3.35	2.52	1.42	7.8044	Black	25 PC
5103.034.232	1"	34.5	M32 x 1.5	0.91	1.73	0.55	3.96	2.91	1.54	11.0231	Black	10 PC
5103.034.240	1"	34.5	M40 x 1.5	1.14	1.73	0.55	3.96	2.91	1.77	11.9049	Black	10 PC
5103.042.240	1 1/4"	42.5	M40 x 1.5	1.24	2.05	0.67	4.37	3.25	1.89	14.7710	Black	10 PC
5103.042.250	1 1/4"	42.5	M50 x 1.5	1.24	2.05	0.67	4.37	3.25	2.32	19.1802	Black	10 PC
5103.054.250	1 1/2"	54.5	M50 x 1.5	1.4	2.52	0.67	4.9	3.86	2.36	22.7076	Black	5 PC
5103.054.263	1 1/2"	54.5	M63 x 1.5	1.79	2.52	0.67	4.9	3.82	2.76	25.7941	Black	5 PC
5103.010.012	1/4"	10	M12 x 1.5	0.26	0.67	0.39	2.24	1.54	0.71	1.7637	Grey	50 PC
5103.013.016	5/16"	13	M16 x 1.5	0.33	0.79	0.47	2.32	1.59	0.83	2.2046	Grey	50 PC
5103.015.020	3/8"	15.8	M20 x 1.5	0.39	0.91	0.47	2.44	1.77	0.94	3.3069	Grey	50 PC
5103.021.020	1/2"	21.2	M20 x 1.5	0.51	1.16	0.47	2.87	1.89	1.02	4.4092	Grey	50 PC
5103.021.025	1/2"	21.2	M25 x 1.5	0.57	1.16	0.51	2.87	1.89	1.02	5.0706	Grey	50 PC
5103.028.025	3/4"	28.5	M25 x 1.5	0.67	1.46	0.51	3.54	2.52	1.26	7.2752	Grey	25 PC
5103.028.032	3/4"	28.5	M32 x 1.5	0.79	1.46	0.55	3.35	2.52	1.42	7.4957	Grey	25 PC
5103.034.032	1"	34.5	M32 x 1.5	0.91	1.73	0.55	3.96	2.91	1.54	11.0231	Grey	10 PC
5103.034.040	1"	34.5	M40 x 1.5	1.14	1.73	0.55	3.96	2.91	1.77	11.9049	Grey	10 PC
5103.042.040	1 1/4"	42.5	M40 x 1.5	1.24	2.05	0.67	4.37	3.25	1.89	14.7710	Grey	10 PC
5103.042.050	1 1/4"	42.5	M50 x 1.5	1.42	2.05	0.67	4.37	3.25	2.32	19.1802	Grey	10 PC
5103.054.050	1 1/2"	54.5	M50 x 1.5	1.4	2.52	0.67	4.9	3.86	2.36	22.7076	Grey	5 PC

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103



Technical Data Sheet

Aerosusa.com
service@aerosusa.com
855.393.9905

"Unsurpassed in Cable Protection and Strain Relief"

2409 Herr St.
Harrisburg, PA 17103