

# 9080GCB01

Circuit protector, Linergy, thermal magnetic overcurrent, track mount, 0.1A, 250 VAC / 65 VDC



## Main

Range of Product	9080GCB
Product or Component Type	Circuit Protector
Trip Unit Type	Thermal-magnetic
Electrical Connection	Box lugs

## Complementary

Protection Type	Overcurrent
Contact operation	Trip-free
Device Application	Industrial Application
Line Rated Current	0.1 A
Number of Poles	1P
Voltage Rating	250 V AC 65 V DC
Wire Size	AWG 16...AWG 10 copper
Wire stripping length	0.5 in (12.70 mm)
Terminal Tightening Torque	Control circuit 7 lbf.in (0.79 N.m) cage type connector
Terminal Rating	Factory wiring only
Operating Temperature	-22...140 °F (-30...60 °C)
Calibration Temperature	70 °F (21 °C)
Mounting Support	35 mm DIN rail 9080GH track
Height	3.45 in (87.63 mm)
Width	3.15 in (80.01 mm)
Depth	0.5 in (12.70 mm)

## Environment

Product Certifications	CSA file 025490 class 3211 07 CE UL recognized E233026 CCN QVNU2
Standards	UL 1077 DIN 57470 CSA C22.2 No 235

## Ordering and shipping details

Category	21703-9080 GCB
Discount Schedule	CP5
GTIN	785901481119
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	DE

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------