

Change Notice


IS Series

Change of LCD of SmartSwitch 36 x 24 Switches & Displays

Type of Change:

- Engineering Part Number
- Product Appearance

LCD change for IS Series standard size LCD 36 x 24 Switches and Displays with yellow LCD mode and black/white LCD mode.



This change will affect the following products including all custom products, Easy Display Kit & Set.

IS15AACP4CF, IS15ABCP4CF, IS15ABCP4E, IS15ABCP4EF, IS15ABFP4B, IS15ABFP4RGB, IS01BCCF, IS01BCE, IS01BCEF, IS01BFRGB

Change of LCD														
Outer Shape	Before Change				After Change									
	Switch		Display		Switch		Display							
Operating Temp					0 ~ +40°C					-20 ~ +60°C				
Storage Temp					-10 ~ +60°C					-30 ~ +70°C				
Operating Voltage		Yellow Mode	B/W Mode	Yellow Mode	B/W Mode	Yellow Mode	B/W Mode	Yellow Mode	B/W Mode	Yellow Mode	B/W Mode			
		7.4V	7.3V	7.3V		7.3V		7.3V		7.3V				
Handling		Solder profile: 270°C max. for 5 seconds max. When soldering take caution that temperature at the LCD does not exceed 60°C. These products are not process sealed.				LCD Temp Characteristics The contrast and speed of LCDs decrease in environments under 0°C. When operating at temperatures above 60°C the LCD can darken.								
						Solder profile: 270°C max. for 5 seconds max. When soldering take caution that temperature at the LCD does not exceed 70°C. These products are not process sealed.								

Availability

Change will be effective immediately.



www.nkkswitches.com
1.877.2BUYNKK (228.9655)

7850 East Gelding Drive • Scottsdale, AZ 85260
Telephone 480.991.0942 • Fax 480.998.1435