

American Data Link

18AWG 2-Conductor Solid White Cable

Technical Data Sheet



Manufacturer Part Number: 182X-WH-NRC
Inspired LED SKU# 3609-B (Bulk, sold by ft.)

Description: 2-Conductor 18 AWG solid bare copper, insulated and jacketed with an overall white sunlight resistant jacket, **with no rip cord**

NEC Rating: FPLR and CMR –NEC Articles 760 and 800

Approvals: c(ETL)us Listed to UL Standards 444 and 1424
Certified to CSA Std. C22.2 No. 214+B4
Complies with European Directive 2002/95/EC RoHS
MSHA approved – CFR Title 30, Part 7, Subpart K, Section 7.408

Flame Rating: UL 1666 Riser Flame Test

Application: Fire alarm power-limited circuit cable and/or communications cable used for riser applications

Construction:

Number of Conductors-	2
Size and Stranding-	18AWG (Solid) Bare Copper
Insulation Material (Nom.)-	0.010" PVC
Color Code-	Black (-), Red (+)
Jacket Material-	0.015" White Sunlight Resistant PVC
Overall Cable Diameter-	0.146"

Print Legend: AMERICAN DATA LINK #182X-WH-NRC 2COND 18AWG FPLR/CMR c(ETL)us
75C SUN RES RoHS P-07-KA090003-MSHA 300V **MADE IN THE USA**

Environmental & Electrical Properties:

Temperature Rating-	-20°C to 75°C
Operating Voltage (Max)-	300 V RMS
Nom. Capacitance btw Cond. @ 1KHz-	29 pf/ft
Nom. DC Resistance per Cond @ 20 C-	6.385 Ohms per 1000 ft

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond ADL control, all recommendations or suggestions are presented without guarantee or responsibility on our part. ADL and their distributors disclaim all liability in connection with the use of information contained herein or otherwise.

Distributed by
inspired LED



inspiredled.com



orders@inspiredled.com



(480) 941-4286