

ISSUE 1; August 2022

Description

- Standard 2 x 1.6mm SMD crystal.
Ceramic package with a seam sealed metal lid, hermetically sealed.

Frequency Parameters

- Frequency 16.0MHz to 50.0MHz
- Frequency Tolerance $\pm 10.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Frequency Stability $\pm 10.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing $\pm 3\text{ppm}$ max per year @ 25°C
- Note 2: For other frequency / specification combinations, please contact our sales offices

Electrical Parameters

- Load Capacitance (CL) 8.0pF to 30.0pF
- Shunt Capacitance (C0) 3pF max
- Drive Level 100µW max
- Note 1: ESR values for reference only. The final spec shall be confirmed for each frequency after sample production

Operating Temperature Ranges

- 0 to 50°C
- 10 to 60°C
- 10 to 70°C
- 20 to 70°C
- 40 to 85°C
- 40 to 105°C
- 40 to 125°C

Environmental Parameters

- Shock: IEC 60068-2-27: 1000G, 1ms, 3 times in each of 3 mutually perpendicular planes
- Vibration: IEC 60068-2-6: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane (total 6hrs)
- Storage Temperature Range: -55 to 125°C

Manufacturing Details


- RoHS Terminations NiAu
- RoHS Reflow 260degC 10s

Ordering Information


- Frequency*
Model*
Frequency Tolerance (@25°C)*
Frequency Stability (over operating temperature range)*
Operating Temperature Range*
Load Capacitance*
Overtone
- Example:
30.0MHz IQXC-42
30/50/-40 to 85C/16 FUND

Compliance

- RoHS Status (2015/863/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable



Outline (mm)



Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

Packaging Details

- Pack Style: RL3K Tape & reel in accordance with EIA-481-D
Pack Size: 3,000
- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Cutt In tape, cut from a reel
Pack Size: 100

Electrical Specification - maximum limiting values

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Over Tone Order	ESR
		°C	ppm		Ω
16.0MHz	19.999999MHz	0 to 50	±10	Fundamental	200
		-10 to 60	±15		200
		-20 to 70	±15		200
		-40 to 85	±20		200
		-40 to 105	±50		200
		-40 to 125	±100		200
20.0MHz	23.999999MHz	0 to 50	±10	Fundamental	120
		-10 to 70	±15		120
		-20 to 70	±15		120
		-40 to 85	±20		120
		-40 to 105	±50		120
		-40 to 125	±100		120
24.0MHz	29.999999MHz	0 to 50	±10	Fundamental	100
		-10 to 70	±15		100
		-20 to 70	±15		100
		-40 to 85	±20		100
		-40 to 105	±50		100
		-40 to 125	±100		100
30.0MHz	37.999999MHz	0 to 50	±10	Fundamental	80
		-10 to 60	±15		80
		-20 to 70	±15		80
		-40 to 85	±20		80
		-40 to 105	±50		80
		-40 to 125	±100		80
38.0MHz	50.0MHz	0 to 50	±10	Fundamental	60
		-10 to 60	±15		60
		-20 to 70	±15		60
		-40 to 85	±20		60
		-40 to 105	±50		60
		-40 to 125	±100		60

*Stability Maximum values ±100ppm

This document was correct at the time of printing; please contact your local sales office for the latest version.
[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200

USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com