


# F611JF182J630C

F611, Film, Metallized Polyester, General Purpose, 1800 pF, 5%, 630 VDC, 85°C, Lead Spacing = 5mm

## FRONT VIEW



Click [here](#) for the 3D model.

### Dimensions

- L 7.2mm -0.5mm
- H 6.5mm -0.5mm
- T 2.5mm -0.5mm
- S 5mm +/-0.4mm
- LL 4mm +2mm

### **Dimensions**

F 0.5mm +/-0.05mm

G 0.5mm NOM

### **Packaging Specifications**

Packaging Bulk

Packaging Quantity 3000

### **General Information**

Series F611

Dielectric Metallized Polyester

Style Radial

Features MKT (Wound), DC Multipurpose Applications

RoHS Yes

Lead Wire Leads

AEC-Q200 No

Miscellaneous The Rated Voltage Decreases 1.25%/C Between +85C And +105C (For +125C, Please Consult Kemet). This 5% tolerance part is available on request.  
ClimCat: 55/105/56.

### **Specifications**

Capacitance 1800 pF

Capacitance Tolerance 5%

Voltage AC 220 VAC

Voltage DC 630 VDC, 472.5 VDC (105C)

Temperature Range -55/+105°C

Rated Temperature 85°C

Dissipation Factor 0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz

Insulation Resistance 30 GOhms

Max dV/dt 80 V/us

Inductance 6 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - 28eef12b-a287-4215-b3ab-cdd4850f31a0

© 2006 - 2023 KEMET

Generated 5/18/2023 - 28eef12b-a287-4215-b3ab-cdd4850f31a0

© 2006 - 2023 KEMET