

3

Safety-Walk™

Wet Area Matting 1500

(Also known as 3M™ Nomad™ Medium Traffic Unbacked Matting)

1.0 Product Description	The product is an unbacked, nonwoven, open and porous matting made from continuous vinyl filaments. Overall, the mat provides antifatigue comfort while collecting dirt and draining water.	
2.0 Intended Use	For use as a comfort cushion for bare feet while allowing water to drain through the matting. 3M Safety-Walk Wet Area Matting 1500 also can be used as a fatigue reducing cushion mat. Applications include locker rooms, shower areas, and around saunas. Not recommended in kitchens or greasy, oily areas.	
3.0 Standard Sizes	Rolls:	3 ft. x 20 ft.
	Custom Lengths:	
	Width:	3 feet
	Length:	2 feet to 40 feet in 1 foot increments
4.0 Color	Blueberry, Spruce	
5.0 Requirements	General Requirements The product shall be made of oil-resistant, all-vinyl, nonwoven continuous filaments bonded together to form a durable, resilient, water-resistant matting.	
	Detailed Requirements:	
	Weight (minimum) ASTM D418-68	3.3 lbs./yd. ² (1.8 kg/m ²)
	Thickness (minimum) [1] ASTM D418-68	0.41 inches (10.3 mm)
	Microbiological Properties ASTM G-21-90	Inhibiting to fungal growth
	Flammability DOC-FF-1-70 (Pill Test)	Passes

5.0 Requirements (continued)

Chemical Resistance[2]	
Water	Excellent [3]
1% Soap	Excellent
50% Ethyl Alcohol	Good
Hydrocarbon Solvents [4]	Poor
Chlorinated Hydrocarbon Solvents [5]	Poor
Gasoline	Poor
Cooking Oil [6]	Poor
5% Acetic Acid	Excellent
5% Sodium Hydroxide	Excellent

[1] Product may be compressed in package. Thickness is manufactured loft before packaging.

[2] All tests 7 days @ 72° F, unless otherwise noted.

[3] Excellent – Slight effect on product, less than 1% weight loss.

Good – Product stiffens or discolors slightly, less than 3% weight loss.

Poor – Product becomes unsuitable for use. 3M™ Safety-Walk™ Matting 1500 should not be used where it will regularly contact these chemicals.

[4] Mineral Spirits.

[5] Methylene Chloride, Perchloroethylene, Chloroform.

[6] Peanut Oil.

6.0 Packaging and Marking

Packaging: One per carton.

Marking: Each carton shall be marked with product name, size, color, and manufacturer's trade name.

7.0 Cleaning

Routine Maintenance:

For Dry Areas:

1. Shake dirt from mat and remove from service area.
2. Sweep and remove dirt from service area.
3. If needed, mop or flush service area.
4. If needed, flush both sides of the mat with warm water to remove remaining dirt.
5. Allow mat to dry flat before placing mat back into service.

For Wet Areas:

Flush both sides of mat daily with warm water.

Periodic Maintenance:

1. Remove mat from service area if needed (no drainage in area).
2. Mop mat(s) on both sides with a disinfectant cleaner and let stand for ten (10) minutes.
3. Flush mat with warm water.
4. Allow mat to dry flat before placing back into service.

8.0 Weight and Cube per Case

Size	Approximate Weight	Cube
3 ft. x 20 ft.	27 lb.	3.5 cu. ft.

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515
Telephone: 907/522-5200
Facsimile: 907/522-1645

CONTINENTAL UNITED STATES

Customer Service Department
3M Center Building 223-5N-07
St. Paul, MN 55144-1000
Order Entry 1-800-852-9722
Facsimile: 1-800-447-0408

HONOLULU

4443 Malaa Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820
Telephone: 808/422-2721
Facsimile: 808/422-9557

3M CANADA

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P.O. Box 5757
London, Ontario, Canada
N6A 4T1
Telephone: 800/364-3577
Facsimile: 800/479-4453

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

3

Commercial Care Division
3M Center
St. Paul, MN 55144-1000

3M, Safety-Walk, and Nomad are trademarks
of 3M.

Copyright © 2001, 3M IPC. All rights reserved.
70-0710-3674-6