



	14 (14-a)	Ag	C091 61G014 110 2 U	C091 61G014 120 2 U	C091 61G014 130 2 U
		Au	C091 61G014 210 2 U	C091 61G014 220 2 U	C091 61G014 230 2 U
	12 (12-a)	Ag	C091 61G012 110 2 U	C091 61G012 120 2 U	C091 61G012 130 2 U
		Au	C091 61G012 210 2 U	C091 61G012 220 2 U	C091 61G012 230 2 U
	8 (08-a)	Ag	C091 61G008 110 2 U	C091 61G008 120 2 U	C091 61G008 130 2 U
		Au	C091 61G008 210 2 U	C091 61G008 220 2 U	C091 61G008 230 2 U
	7 (07-b)	Ag	C091 61G107 110 2 U	C091 61G107 120 2 U	C091 61G107 130 2 U
		Au	C091 61G107 210 2 U	C091 61G107 220 2 U	C091 61G107 230 2 U
	7 (07-a)	Ag	C091 61G007 110 2 U	C091 61G007 120 2 U	C091 61G007 130 2 U
		Au	C091 61G007 210 2 U	C091 61G007 220 2 U	C091 61G007 230 2 U
	6 (06-a)	Ag	C091 61G006 110 2 U	C091 61G006 120 2 U	C091 61G006 130 2 U
		Au	C091 61G006 210 2 U	C091 61G006 220 2 U	C091 61G006 230 2 U
	5 (05-b)	Ag	C091 61G105 110 2 U	C091 61G105 120 2 U	C091 61G105 130 2 U
		Au	C091 61G105 210 2 U	C091 61G105 220 2 U	C091 61G105 230 2 U
	5 (05-a)	Ag	C091 61G005 110 2 U	C091 61G005 120 2 U	C091 61G005 130 2 U
		Au	C091 61G005 210 2 U	C091 61G005 220 2 U	C091 61G005 230 2 U
	4 (04-a)	Ag	C091 61G004 110 2 U	C091 61G004 120 2 U	C091 61G004 130 2 U
		Au	C091 61G004 210 2 U	C091 61G004 220 2 U	C091 61G004 230 2 U
	3 (03-a)	Ag	C091 61G003 110 2 U	C091 61G003 120 2 U	C091 61G003 130 2 U
		Au	C091 61G003 210 2 U	C091 61G003 220 2 U	C091 61G003 230 2 U
Contact arrangement View on mating side	Number of contacts (Contact arrangement acc. DIN EN 61076-2-106)		a = 10,5 mm		
			a = 14,5 mm		
			a = 19,5 mm		

D	Number of contacts	Standard	3	4	5	5S	6	7	7	8	12	14	
	Contact arrangement	DIN EN 61076-2-106	03-a	04-a	05-a	05-b	06-a	07-a	07-b	08-a	12-a	14-a	
C	Contact arrangement	IEC 60130-9 ¹⁾	yes	no	yes	no	yes	no	yes	no			
	Rated voltage ²⁾	IEC 60664-1	300 V (100 V)	300 V (63 V)	100 V (32 V)	300 V (63 V)	100 V (32 V)	150 V (32 V)					
	Rated voltage	UL 1977	250 V							60 V			
	Rated impulse withstand voltage ²⁾	IEC 60664-1	1500 V (840 V)	1200 V (500 V)	1500 V (840 V)	1200 V (500 V)							
	Pollution degree ²⁾	IEC 60664-1	1 (3 ³⁾)										
	Installation category	IEC 60664-1	I										
	Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600										
	Current rating	IEC 60512-5-2 UL 1977	10A/+40°C	7A/+40°C					3A/+40°C				
	Insulation resistance	IEC 60512-3-1	>10 ¹⁰ Ohm ⁴⁾										
	Contact resistance	IEC 60512-2-1	<5m Ohm										
Climatic category	IEC 60668-1	40 / 100 / 56											
Temperatur range	IEC 60668-1	-40°C...+100°C / -40°F...+212°F											
salt spray resistance	DIN IEC 60068-2-11	720h											
IP degree	IEC 60529	IP 69K / IP 67 / IP 65 (in mated condition)											
Insertion and withdrawal force	IEC 60512-13-2	25N	30N	35N	50N	55N	60N	50N					
Mechanical operation	IEC 60512-9-1	Silver ≥500 mating cycles / Gold ≥1000 mating cycles											
Housing material		brass and / or zinc die cast, nickel plated											
Dielectric material		thermoplastic											
Contacts		silver plated / gold plated											
Termination technique		solder											
wire gauge		≤ 0,5mm ² / 20 AWG										≤0,35mm ² /24AWG	
Flamability		UL 94 VO											
locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7 - 1,5 Nm											

¹⁾ Edition 2000-05
²⁾ values in brackets are according to DIN EN 61076-2-106
³⁾ designed acc. pollution degree 2; can be used under pollution degree 3 when the rules of IEC 60664-1 are fulfilled
⁴⁾ under operating conditions >10⁸ Ohm

Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.
 Remark for gold plated contacts:
 In order to avoid brittle inter-metallic connections, gold plated terminals have to be tin-plated in the solder area.
 All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guaranties ("Beschaffungsgarantie" or "Haltbarkeitsgarantie").

Gewicht (errechnet) / Calc WT: 13,72 g	Zul. Abw./Tolerances:	Maßstab / Scale: 2:1	A3	
Prüfmaß / Testdimension	ISO 2768-mH	CUSTOMER DRAWING		
Teileindex / Partindexnumber:	DIN / ISO 13715	Gerätedose Rückwandmontage female receptacle rear mount.		
Bagatelle change:	Gez. 14.10.2015 Drawn MTOLKSDORF	Blatt/Sheet 1		
	Status Released	1 Bl.		
	Gepr. 21.10.2020 Checked MGRIMM	Ers. f. l. Replacement for: M-C091 61GXXX X10 2 U Rev.01		
03 202000001 21.10.2020 MCARL	Amphenol Tuchel Industrial GmbH	M C091 61GXXX XX0 2 U		
02 201500721 14.10.2015 MTOLK				
Index Änderung/Description Datum/Date Name				

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

FAI2020-003905
NXM-V04