

# IGBT - Ultra Field Stop

## 1200 V, 40 A, $V_{CE(Sat)} = 1.55V$ , TO247 4L

### FGH4L40T120LQD

This Insulated Gate Bipolar Transistor (IGBT) features a robust and cost-effective Ultra Field Stop Trench construction, and provides superior performance in demanding switching applications, offering both low on-state voltage and minimal switching loss. The IGBT is well suited for motor driver applications. Incorporated into the device is a soft and fast co-packaged free-wheeling diode with a low forward voltage.

#### Features

- Extremely Efficient Trench with Field Stop Technology
- Maximum Junction Temperature:  $T_J = 175^{\circ}C$
- Fast and Soft Reverse Recovery Diode
- Optimized for Low  $V_{CE(Sat)}$

#### Typical Applications


- Solar Inverter and UPS
- Industrial Switching
- Welding

#### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CE}$	1200	V
Gate-Emitter Voltage Transient Gate-Emitter Voltage	$V_{GE}$	$\pm 20$ $\pm 30$	V
Collector Current @ $T_C = 25^{\circ}C$ (Note 1) @ $T_C = 100^{\circ}C$	$I_C$	80 40	A
Pulsed Collector Current (Note 2)	$I_{LM}$	160	A
Pulsed Collector Current (Note 3)	$I_{CM}$	160	A
Diode Forward Current @ $T_C = 25^{\circ}C$ (Note 1) @ $T_C = 100^{\circ}C$	$I_F$	80 40	A
Maximum Power Dissipation @ $T_C = 25^{\circ}C$ @ $T_C = 100^{\circ}C$	$P_D$	306 153	W
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to +175	$^{\circ}C$
Maximum Lead Temp. for Soldering Purposes (1/8" from case for 5 s)	$T_L$	260	$^{\circ}C$


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Value limit by bond wire
2.  $V_{CC} = 600V$ ,  $V_{GE} = 15V$ ,  $I_C = 160A$ ,  $R_G = 15\Omega$ , Inductive Load, 100% Tested
3. Repetitive rating: Pulse width limited by max. junction temperature




TO-247-4LD  
CASE 340CJ

#### MARKING DIAGRAM



FGH40T120LQD = Specific Device Code  
 $\$Y$  = onsemi Logo  
 $\&Z$  = Assembly Plant Code  
 $\&3$  = 3-Digit Date Code  
 $\&K$  = 2-Digit Lot Traceability Code

#### PIN CONNECTIONS



#### ORDERING INFORMATION

Device	Package	Shipping
FGH4L40T120LQD	TO-247	30 Units / Rail

# FGH4L40T120LQD

## THERMAL CHARACTERISTICS

Rating	Symbol	Min	Typ	Max	Unit
Thermal resistance junction-to-case, for IGBT	$R_{\theta JC}$	-	0.38	0.49	$^{\circ}\text{C}/\text{W}$
Thermal resistance junction-to-case, for Diode	$R_{\theta JC}$	-	0.64	0.84	$^{\circ}\text{C}/\text{W}$
Thermal resistance junction-to-ambient	$R_{\theta JA}$	-	-	40	$^{\circ}\text{C}/\text{W}$

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
<b>OFF CHARACTERISTIC</b>						
Collector-Emitter Breakdown Voltage	$V_{GE} = 0\text{ V}, I_C = 1\text{ mA}$	$BV_{CES}$	1200	-	-	V
Temperature Coefficient of Breakdown Voltage	$V_{GE} = 0\text{ V}, I_C = 1\text{ mA}$	$\Delta BV_{CES} / \Delta T_J$	-	1.3	-	$\text{V}/^{\circ}\text{C}$
Collector-Emitter Cut-Off Current	$V_{GE} = 0\text{ V}, V_{CE} = 1200\text{ V}$	$I_{CES}$	-	-	40	$\mu\text{A}$
Gate Leakage Current	$V_{GE} = 20\text{ V}, V_{CE} = 0\text{ V}$	$I_{GES}$	-	-	200	nA

## ON CHARACTERISTIC

Gate-Emitter Threshold Voltage	$V_{GE} = V_{CE}, I_C = 40\text{ mA}$	$V_{GE(th)}$	5.5	6.5	7.5	V
Collector-Emitter Saturation Voltage	$V_{GE} = 15\text{ V}, I_C = 40\text{ A}, T_J = 25^{\circ}\text{C}$	$V_{CE(sat)}$	-	1.55	1.80	V
	$V_{GE} = 15\text{ V}, I_C = 40\text{ A}, T_J = 175^{\circ}\text{C}$		-	2	-	

## DYNAMIC CHARACTERISTIC

Input Capacitance	$V_{CE} = 30\text{ V}, V_{GE} = 0\text{ V}, f = 1\text{ MHz}$	$C_{ies}$	-	5079	-	pF
Output Capacitance		$C_{oes}$	-	113	-	
Reverse Transfer Capacitance		$C_{res}$	-	62	-	
Gate Charge Total	$V_{CC} = 600\text{ V}, I_C = 40\text{ A}, V_{GE} = 15\text{ V}$	$Q_g$	-	227	-	nC
Gate-to-Emitter Charge		$Q_{ge}$	-	40	-	
Gate-to-Collector Charge		$Q_{gc}$	-	108	-	

## SWITCHING CHARACTERISTIC, INDUCTIVE LOAD

Turn-on Delay Time	$T_J = 25^{\circ}\text{C}$ $V_{CC} = 600\text{ V}, I_C = 20\text{ A}$ $R_g = 10\ \Omega$ $V_{GE} = 15\text{ V}$ Inductive Load	$t_{d(on)}$	-	38	-	ns	
Rise Time		$t_r$	-	13	-		
Turn-off Delay Time		$t_{d(off)}$	-	227	-		
Fall Time			$t_f$	-	51	-	mJ
Turn-on Switching Loss		$E_{on}$	-	0.63	-		
Turn-off Switching Loss		$E_{off}$	-	0.77	-		
Total Switching Loss		$E_{ts}$	-	1.40	-		
Turn-on Delay Time	$T_J = 25^{\circ}\text{C}$ $V_{CC} = 600\text{ V}, I_C = 40\text{ A}$ $R_g = 10\ \Omega$ $V_{GE} = 15\text{ V}$ Inductive Load	$t_{d(on)}$	-	42	-	ns	
Rise Time		$t_r$	-	19	-		
Turn-off Delay Time		$t_{d(off)}$	-	218	-		
Fall Time			$t_f$	-	80	-	mJ
Turn-on Switching Loss		$E_{on}$	-	1.04	-		
Turn-off Switching Loss		$E_{off}$	-	1.35	-		
Total Switching Loss		$E_{ts}$	-	2.39	-		

# FGH4L40T120LQD

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
<b>SWITCHING CHARACTERISTIC, INDUCTIVE LOAD</b>						
Turn-on Delay Time	$T_J = 175^\circ\text{C}$ $V_{CC} = 600\text{ V}, I_C = 20\text{ A}$ $R_g = 10\ \Omega$ $V_{GE} = 15\text{ V}$ Inductive Load	$t_{d(on)}$	-	32	-	ns
Rise Time		$t_r$	-	12	-	
Turn-off Delay Time		$t_{d(off)}$	-	264	-	
Fall Time		$t_f$	-	156	-	
Turn-on Switching Loss		$E_{on}$	-	1.05	-	mJ
Turn-off Switching Loss		$E_{off}$	-	1.62	-	
Total Switching Loss		$E_{ts}$	-	2.67	-	
Turn-on Delay Time	$T_J = 175^\circ\text{C}$ $V_{CC} = 600\text{ V}, I_C = 40\text{ A}$ $R_g = 10\ \Omega$ $V_{GE} = 15\text{ V}$ Inductive Load	$t_{d(on)}$	-	36	-	ns
Rise Time		$t_r$	-	20	-	
Turn-off Delay Time		$t_{d(off)}$	-	236	-	
Fall Time		$t_f$	-	204	-	
Turn-on Switching Loss		$E_{on}$	-	1.62	-	mJ
Turn-off Switching Loss		$E_{off}$	-	2.51	-	
Total Switching Loss		$E_{ts}$	-	4.13	-	


## DIODE CHARACTERISTIC

Forward Voltage	$V_{GE} = 0\text{ V}, I_F = 40\text{ A}, T_J = 25^\circ\text{C}$	$V_F$	-	3.31	3.80	V
	$V_{GE} = 0\text{ V}, I_F = 40\text{ A}, T_J = 175^\circ\text{C}$		-	2.97	-	
Reverse Recovery Energy	$T_J = 25^\circ\text{C}$ $I_F = 40\text{ A}, V_R = 600\text{ V}$ $di_F/dt = 1000\text{ A}/\mu\text{s}$	$E_{REC}$	-	126	-	$\mu\text{J}$
Diode Reverse Recovery Time		$T_{rr}$	-	59	-	ns
Diode Reverse Recovery Charge		$Q_{rr}$	-	804	-	nC
Reverse Recovery Energy	$T_J = 175^\circ\text{C}$ $I_F = 20\text{ A}, V_R = 600\text{ V}$ $di_F/dt = 1000\text{ A}/\mu\text{s}$	$E_{REC}$	-	540	-	$\mu\text{J}$
Diode Reverse Recovery Time		$T_{rr}$	-	115	-	ns
Diode Reverse Recovery Charge		$Q_{rr}$	-	2090	-	nC
Reverse Recovery Energy	$T_J = 175^\circ\text{C}$ $I_F = 40\text{ A}, V_R = 600\text{ V}$ $di_F/dt = 1000\text{ A}/\mu\text{s}$	$E_{REC}$	-	667	-	$\mu\text{J}$
Diode Reverse Recovery Time		$T_{rr}$	-	127	-	ns
Diode Reverse Recovery Charge		$Q_{rr}$	-	2613	-	nC


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# FGH4L40T120LQD


## TYPICAL CHARACTERISTICS




**Figure 1. Typical Output Characteristics**  
( $T_J = 25^\circ\text{C}$ )




**Figure 2. Typical Output Characteristics**  
( $T_J = 175^\circ\text{C}$ )




**Figure 3. Typical Saturation Voltage Characteristics**



**Figure 4. Typical Transfer Characteristics**



**Figure 5. Saturation Voltage vs. Junction Temperature**



**Figure 6. Capacitance Characteristics**

# FGH4L40T120LQD

## TYPICAL CHARACTERISTICS




Figure 7. Gate Charge Characteristics




Figure 8. SOA Characteristics (FBSOA)




Figure 9. Turn-on Characteristics vs. Gate Resistance




Figure 10. Turn-off Characteristics vs. Gate Resistance




Figure 11. Turn-on Characteristics vs. Collector Current




Figure 12. Turn-off Characteristics vs. Collector Current

# FGH4L40T120LQD

## TYPICAL CHARACTERISTICS




Figure 13. Switching Loss vs. Gate Resistance




Figure 14. Switching Loss vs. Collector Current




Figure 15. (Diode) Forward Characteristics




Figure 16. (Diode) Reverse Recover Current vs. Forward Current




Figure 17. (Diode) Reverse Recovery Time




Figure 18. (Diode) Stored Charge

# FGH4L40T120LQD

## TYPICAL CHARACTERISTICS




Figure 19. Transient Thermal Impedance of IGBT




Figure 20. Transient Thermal Impedance of Diode

FGH4L40T120LQD




Figure 21. Test Circuits for Switching Characteristics




Figure 22. Definition of Turn-On Waveforms



# FGH4L40T120LQD




Figure 23. Definition of Turn-Off Waveforms

# MECHANICAL CASE OUTLINE


## PACKAGE DIMENSIONS

ON Semiconductor®



TO-247-4LD  
CASE 340CJ  
ISSUE A

DATE 16 SEP 2019



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.80	5.00	5.20
A1	2.10	2.40	2.70
A2	1.80	2.00	2.20
b	1.07	1.20	1.33
b1	1.20	1.40	1.60
b2	2.02	2.22	2.42
c	0.50	0.60	0.70
D	22.34	22.54	22.74
D1	16.00	16.25	16.50
D2	0.97	1.17	1.37
e	2.54 BSC		
e1	5.08 BSC		
E	15.40	15.60	15.80
E1	12.80	13.00	13.20
E/2	4.80	5.00	5.20
L	18.22	18.42	18.62
L1	2.42	2.62	2.82
p	3.40	3.60	3.80
p1	6.60	6.80	7.00
Q	5.97	6.17	6.37
S	5.97	6.17	6.37

NOTES:

- A. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE.
- B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- C. ALL DIMENSIONS ARE IN MILLIMETERS.
- D. DRAWING CONFORMS TO ASME Y14.5-2009.

<b>DOCUMENT NUMBER:</b>	<b>98AON13852G</b>	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
<b>DESCRIPTION:</b>	<b>TO-247-4LD</b>	<b>PAGE 1 OF 1</b>

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)