



- △ 2.54um[.000100] MIN TIN-LEAD OVER 1.27um[.000050] MIN NICKEL.
- △ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 6.35[.250] FROM MATING END WITH GOLD FLASH ON REMAINDER, ALL OVER 1.27um[.000050] MIN NICKEL.
- △ POSTS ARE SEMI-AUTOMATICALLY WIREABLE AND WILL ACCOMODATE (SEE TABLE) TERMINATIONS.
- 4. #24 AWG MAX WIRE TO BE USED WITH THIS CONNECTOR.
- △ AMP, PART NUMBER, DATE CODE & THE LETTER P INK STAMPED IN THIS AREA.
- △ 2.54um[.000100] MIN TIN OVER 1.27um[.000050] MIN NICKEL.

△	6.63 [.261]	1	3-205317-5
△	16.74 [.659]	3	3-205317-4
△	6.63 [.261]	1	3-205317-1
△	16.74 [.659]	3	205317-1
POST PLATING	A	NO OF TERM	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± 0.13 [.005] 3 PLC ± - 4 PLC ± - ANGLES ± -	FINISH SEE CALLOUTS	DWN C. REIFSNYDER 08 FEB 96 CHK R. STONE 22 FEB 96 APVD W. MCALONIS 22 FEB 96 NAME Tyco Electronics Corporation Harrisburg, Pa 17105-3608 PIN ASSY, 14 POSITION, AUTOWIREABLE, STANDARD M SERIES	SIZE A1 CAGE CODE 00779 DRAWING NO. 205317 RESTRICTED TO
MATERIAL SEE CALLOUTS	WEIGHT -	CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1