

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# 8-Port 10/100/1000 Mbps Desktop Gigabit Ethernet Unmanaged Switch

MODEL NUMBER: NG8P











Energy-efficient unmanaged switch sets up in seconds with no configuration required. Provides a Gigabit network connection for multiple devices. Ideal for home or small offices, workgroups and creative production environments.

#### Description

The NG8P 8-Port 10/100/1000 Mbps Desktop Gigabit Ethernet Unmanaged Switch adds 10/100/1000 Mbps Ethernet capacity to your home office, small office, workgroup or creative production environment. Share large bandwidth-intensive files, such as CAD drawings and videos, at Gigabit speeds, improving efficiency and cutting costly downtime.

This desktop switch features eight twisted-pair RJ45 Gigabit Ethernet ports that support auto-negotiable 10/100/1000 Mbps and auto MDI/MDIX cross-over detection functions for convenient plug-and-play capability. No configuration is required, so you can have your Gigabit network up and running immediately. Easy-to-read LEDs indicate connection and activity status for each port. IEEE 802.3x flow control allows smooth transmission of large files.

The NG8P supports IEEE 802.3az Energy Efficient Ethernet standards by putting unused ports into a low-power state without interrupting network connections. It consumes very little input power—just a single watt. The detachable five-foot input cord with NEMA 1-15P plug connects to a protected UPS, generator or mains input AC source.

#### **Features**

Unmanaged Network Switch for Home/Small Offices or Workgroups8 twisted-pair RJ45 Gigabit Ethernet portsAuto-negotiable 10/100/1000 MbpsAutomatic MDI/MDIX cross-over detection16 Gbps switching capacity (2 Gbps per port with full duplex)Easy-to-read LEDs indicate connection and activity status for each portSupports 9k jumbo framesMAC address table capacity of up to 4k addresses with automatic learning and agingSupports 802.3x flow control (full duplex) and back pressure (half duplex)

Compliant with IEEE 802.3az Energy Efficient Ethernet Standards Automatically shifts unused ports to

#### **Highlights**

- 8 auto-negotiable 10/100/1000 Mbps RJ45 ports
- Supports auto MDI/MDIX crossover function
- Consumes very little input power—just 1W
- 2 Gbps switching capacity per port with full duplex
- Plug and play with no configuration required

### **Package Includes**

- NG8P 8-Port 10/100/1000 Mbps Desktop Gigabit Ethernet Unmanaged Switch
- External power supply w/NEMA 1-15P plug and 5 ft. cord
- · Owner's manual



low-power state without interrupting network connectionConsumes very little input power—just 1WAlso meets IEEE 802.3ab, 802.3i, 802.3u and 802.3 standards

**Durable Housing**Fanless design for silent operationDetachable 5 ft. AC power cord with NEMA 1-15P plugPlug-and-play—no configuration necessary

## **Specifications**

OVERVIEW		
UPC Code	037332194749	
Product Type	Unmanaged Switch	
INPUT		
Electrical Consumption (Max)	1W	
Nominal Input Voltage Description	Included 5V DC output power adapter accepts 100-240V AC nominal input	
Plug Type	Power adapter includes NEMA 1-15P non-polarized input plug	
Voltage Compatibility (VAC)	100-240	
Input Plug Type	NEMA 1-15P	
Input Cord Length (ft.)	5	
Input Cord Length (m)	1.52	
USER INTERFACE, ALERTS & COI	NTROLS	
LED Indicators	Power LED (Green for Power On); One LED per RJ45 port (Green, LEDs flash to indicate port activity)	
PHYSICAL		
Primary Form Factor	Desktop	
Color	Black	
Form Factors Supported	Desktop	
Material of Construction	Plastic	
Shipping Dimensions (hwd / cm)	7.87 x 7.62 x 12.95	
Shipping Dimensions (hwd / in.)	3.10 x 3.00 x 5.10	
Shipping Weight (kg)	0.24	
Shipping Weight (lbs.)	0.53	
Unit Dimensions (hwd / cm)	2.2 x 12.5 x 6.5	
Unit Dimensions (hwd / in.)	.87 x 4.92 x 2.56	
Unit Weight (kg)	0.11	
Unit Weight (lbs.)	.25	
Rack Units	0	



ENVIRONMENTAL		
Storage Temperature Range	14 to 158F (-10 to 70C)	
Relative Humidity	10 to 90% (non-condensing)	
Operating Temperature	32 to 104F (0 to 40C)	
Power Consumption (Watts)	1	
Fans (Type/Quantity)	Fanless	
COMMUNICATIONS		
Network Compatibility	Gigabit Ethernet (10/100/1000)	
Network Compatibility Details	Auto-negotiable	
Switching Capacity	16 Gbps	
Switching Capacity Details	2 Gbps per port with full duplex	
CONNECTIONS		
RJ45 Ports	8	
RJ45 Ports Detail	8x 10/100/1000BASE-T	
SFP Uplink Ports	0	
PoE Supported Ports	0	
Network Switch Ports	(8) 10/100/1000 (RJ45)	
FEATURES & SPECIFICATIONS		
MAC Addresses	4000	
Jumbo Frames	9000	
Console Port	No	
MAC Auto Learning	No	
RMON	No	
SNMP	No	
Storm Control	No	
DHCP Snooping	No	
Auto MDI/MDIX Crossover Detection	Yes	
STANDARDS & COMPLIANCE		
Certifications	Compliant Standards: IEEE 802.3ab (1000BASE-T GIGABIT ETHERNET), IEEE 802.3i (10BASE-T ETHERNET), IEEE 802.3u (100BASE-T ETHERNET), IEEE 802.3x (FULL DUPLEX/FLOW CONTROL), IEEE 802.3 (NWAY AUTO-NEGOTIATION), 802.3az (ENERGY EFFICIENT ETHERNET)	
Approvals	Tested to North American and International safety and EMI standards EN 60950-1: 2006+A11:2009+A12:2011; FCC CLASS B, EN55022:2010, EN55024:2010, NOM, RoHS Compliant	



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>