


THIS SERIES FULLY CONFORMS TO


THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

## .XX ±0.13 .XXX ±0.05




## NOTES:

| MATERIAL:<br>HOUSING:<br>SHELL:<br>CONTACT:                  | THERMOPLASTIC POLYESTER, UL94V-0<br>STEEL, NICKEL PLATED<br>COPPER ALLOY, 30µ GOLD PLATED |
|--|---|
| OPERATING TEMPERATURE:                                       | -55°C ~ 125°C   |
| POWER/CO-AX CONTACT RATING:<br>(IF PRESENT)                  | 40A (CURRENT)   |
| SIGNAL CONTACT CURRENT RATING:<br>SIGNAL CONTACT RESISTANCE: | 5A PER CONTACT<br>10mΩ MAX.   |
| INSULATOR RESISTANCE:<br>DIELECTRIC                          | 5000MΩ min.   |
| WITHSTANDING VOLTAGE:  | 1000V AC rms  |



|                            |  |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                    |            |       |
|----------------------------|--|--|--------------------------------------|--------------------|------------|-------|
| COMBINATION D-SUB          |  | DRAWN: C.B   |                                      | DATE: JAN. 01/2019 |            |       |
|                            |  | CHECKED:   |                                      | DATE:              |            |       |
|                            | EDAG INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE:                               | (IN C.A.D. 1:1)    | SHEET 1 OF | 2     |
|                            |  |  | DRAWING NUMBER: 630-2W2-650-4N5      |                    | -650-4N5   | ISSUE |
| YOUR CONNECTION TO QUALITY |  |  | PART NU                              | MBER: 630-2W2-     | -650-4N5   | 1     |



J

COMPLIANT

