



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours
- Mass : 60.21 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 26.97         |
| R2                  | 24.61         |
| S                   | 33.3±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M25x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D017S06PNL**

|                |   |                                |   |
|----------------|---|--------------------------------|---|
| B              | 11-04-17                                    | Drawing Update                 |   |
| ISS            | DATE  | Latest modification - by       | MOD N°  |
| Designed By:   |   | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                                |   |
| SCALE          | NA  | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>A3</b>                                   |                                | SHEET<br>1/2  |
|                |   | <b>SOURIAU DRG N°</b>          |   |
|                |   | <b>8D017S06PNL-C</b>           |   |

|                |                          |   |   |    |   |                                 |   |   |   |                        |
|----------------|--------------------------|---|---|----|---|---------------------------------|---|---|---|------------------------|
| BASIC SERIES:  | 8D                       | 0 | - | 17 | S | 06                              | P | N | L | Delivered W/O Contacts |
| SHELL TYPE :   | Square Flange Receptacle |   |   |    |   | ORIENTATION : N                 |   |   |   |                        |
| CONTACT TYPE : | Standard Crimp Contact   |   |   |    |   | CONTACT TYPE : PIN(500 Matings) |   |   |   |                        |
| SHELL SIZE :   | 17                       |   |   |    |   | CONTACT LAYOUT : 17-06          |   |   |   |                        |
| PLATING :      | S = Nickel               |   |   |    |   |                                 |   |   |   |                        |

Contact Layout



| Contacts<br>(Insert arrangement 17-6) |             |             |
|---------------------------------------|-------------|-------------|
| Contact position ID                   | Location    |             |
|                                       | X-axis (mm) | Y-axis (mm) |
| A                                     | +121 (3.07) | +209 (5.31) |
| B                                     | +241 (6.12) | +000 (0.00) |
| C                                     | +000 (0.00) | -241 (6.12) |
| D                                     | -241 (6.12) | +000 (0.00) |
| E                                     | -121 (3.07) | +209 (5.31) |
| F                                     | +000 (0.00) | +000 (0.00) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 17         | -6              | 6                  | 12            | I              | All              | MS20053-6  |

Panel Cutout



Max. thickness panel for receptacle: Type 0: front mounting = 3.2 mm, rear mounting = 2.5 mm

| Dim | Nominal    |
|-----|------------|
| ØA  | 30.96 min  |
| ØAA | 25.81 min  |
| R1  | 26.97      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D017S06PNL

|                |                                      |                            |   |
|----------------|--------------------------------------|----------------------------|---|
| B              | 11-04-17                             | Drawing Update             |   |
| ISS            | DATE                                 | Latest modification - by   | MOD N°  |
| Designed By:   |                                      | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Stainless Steel Receptacle 8D series |                            |   |
| SCALE          |                                      | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                      | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | WWW.SOURIAU.COM                      |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | SOURIAU DRG N° 8D017S06PNL-C         |                            | SHEET 2/2   |