

1

2

3

4

5

6

7

A

A

B

B

C

C

D

D

E

E

F

F

G

G

H

H

Specifications:

Material:

Housing: Poly Carbonate(PC) UL94V-2
 Contact: Phosphor Bronze with 2 prongs
 Plating: 50u" gold plated
 100u" Nickel under plated
 Operating temperature: -40°C to +125°C


Electrical:

Current rating: 250V AC max. at 2A
 Dielectric: 500V AC
 Insulation resistance: 500MΩ
 Termination resistance: 35mΩ max after environmental tests
 Tensile strength: 20 LBS (89N) min.
 Durability: 500 mating cycles

Complies with FCC68/F

① Wire gauge: 30AWG-24AWG Stranded wire
 Cable OD size: flat cable 2.5x5.0±0.02mm
 Wire size: 0.95±0.05mm

RoHS compliant
 Unit: mm

Scale	Free				Date	Name	Customer-No.	
TOLERANCE				Drawn	13.06.2016	Winnie		
X.X	±0.20			Approved	03.04.2019	Amy	ASSMANN WSW-No.	
X.XX	±0.10						A-MO 6/4-F50	
X.XXX	±0.05						Drawing-No.	
DIM	TOL	① Add cable wire size information	03.04.2019	Amy			ASS 7275 CO	rev01
Angle	±2°	② Drawn	13.06.2016	Winnie			Replace	Sheet
Angle	TOL	Id.	Modification	Date	Name			

1

2

3

4

5

6

7