


SUGGESTED PCB LAYOUT



ACTUATOR	A	09/11/16	CAB
BODY	A	09/11/16	CAB
MATERIALS	A	09/11/16	CAB
PACKAGING	A	09/11/16	CAB
SPECIFICATIONS	B	10/04/07	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

A	INITIAL RELEASE	19207	10/07/20	CAB
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

PACKAGING
 PACKAGING TYPE:
 Tape and Reel
 REEL QUANTITY:
 500 Pieces

SCHEMATIC

POSITION	TERMINAL			
	1	2	4	8
0				
1	●			
2		●		
3	●			
4			●	
5	●			
6		●	●	
7	●		●	
8				●
9	●			
A		●		●
B	●			●
C			●	●
D	●			●
E		●	●	●
F	●	●	●	●

● CLOSED (Connected to C)

SPECIFICATIONS

FUNCTION:
 1P16T

RATINGS:
 Switching: 25mA 24VDC
 Steady: 100mA 50VDC

OPERATING FORCE:
 400gfc

CONTACT RESISTANCE:
 Initial: 100mΩ Max.
 After Life: 200mΩ Max.

INSULATION RESISTANCE:
 100MΩ Min. at 250VDC

DIELECTRIC STRENGTH:
 250VAC For 1 Minute

CAPACITANCE:
 5pF Max.

SHOCK RESISTANCE:
 Mil-Std. 202F, Method 213B
 Gravity: 50G, 11msec.
 Direction: 6 Sides
 Times: 3 Each Direction
 High Reliability

VIBRATION RESISTANCE:
 Mil-Std. 202F, Method 201A
 Frequency: 10-55-10Hz/1 Minute
 Direction: X, Y, Z
 Time: 2 Hours Each Direction
 High Reliability

ELECTRICAL LIFE:
 20,000 Steps

TEMPERATURE:
 Storage: -40°C to 85°C
 Operation: -25°C to 80°C


APPROVALS:
RoHS LEAD FREE
 COMPLIANT PROCESS COMPATIBLE

COLORS

BODY:
 Black
 ACTUATOR:
 White
 MARKING COLOR:
 White

MATERIALS

BASE:
 Polyamide 9T (PA9T), UL94 V-0
 COVER:
 Polyamide 9T (PA9T), UL94 V-0
 ACTUATOR:
 Liquid Crystal Polymer (LCP), UL94 V-0
 SPRINGS:
 Stainless Steel
 CONTACTS:
 Gold Over Nickel Plated Phosphor Bronze
 TERMINALS:
 Gold Over Nickel Plated Brass



DIMENSIONS	TITLE
INCHES [MILLIMETERS]	DR3MS-16R-TR
GENERAL TOLERANCES	
±0.008 [±0.2] / ±1'	
SCALE	PROJECTION
DRAWING NOT TO SCALE	1st Angle
ITEM NUMBER	DATE
06-DR3MS16RTR	JULY 20, 2010
REVISION	
A	