ت ت ا	т п		0			
ØS-						
	Keying Shown as example		LAY	OUT SHOWN AS EXAMPLE		
CHARACTERISTICS	Connector dimension	7				
 -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum 	DimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g		due to a use the Specifications	not be liable for any non-conform of the Products which does not of issued by either of the Parties of onal recommendation, technical Country Juri FR	comply with r by a third party	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521M42PE			
-Temperature Range : -65°C to +200°C			08-10-2016 First Release			
-Salt Spray : 2000 hours		ISS Designe	DATE Latest modificatio	n - by	CUSTOMER DRAWING	MOD N°
	TITLE Composite Plug 8D series		8D series			
BASIC SERIES: 8D 5 - 21 M 42 SHELL TYPE : Plug with RFI Shielding - 21 M 42	P E	SCA NA	- [(⊕)	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the prop	perty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 21	ORIE CONTACT TYPE : PIN(5			SOURIAU.COM	it must not be reproduc communicated without pe	ed or
PLATING : M = Nickel	CONTACT TYPE . PIN(S			SOURIAU DRG N	>	SHEET
		_ /``	-	8D521M42PE-C		1/2

	工	G	гт –	m	D	0	
4	(Contact Layout 42					
	Ctc A B	2#4 Power 21-42 X Y 0 6.19 0 -6.19					
ω							
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	oducts wh either o mmendat
0						PN: 8D	Countr FR
					A 08-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
_ _					SCALE NA	Genera Tolera	Compc al linear ances:
					FORMAT A3	SOU	
	Н	G	F	E	D	C C	

