



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 51.41 g ± 10%

| Connector dimension | |
|---------------------|---------------|
| Dim | Nominal |
| P | 3.91±0.2 |
| PP | 6.15±0.2 |
| R1 | 38.1 |
| R2 | 34.93 |
| S | 46±0.3 |
| V | 20.07+0/-1.25 |
| W | 2.1/3.2 |
| Z | 31.5 Max |
| VV THREAD | M37x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D025Z37PN

| | | | |
|--------------|------------|--------------------------|-------------------------|
| A | 10-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |

| | | | |
|--------------|---------------------------------------|--|--|
| TITLE | Aluminium Receptacle 8D series | | |
|--------------|---------------------------------------|--|--|

| | | | |
|-------|--|----------------------------|-----------------|
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |

| | | |
|----------------|------------------------|---|
| SOURIAU | WWW.SOURIAU.COM | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|

| | | |
|-----------|------------------------------------|------------|
| FORMAT | SOURIAU DRG N° 8D025Z37PN-C | SHEET |
| A3 | | 1/2 |

BASIC SERIES: 8D 0 - 25 Z 37 P N

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 25

PLATING : Z = Black Zinc Nickel

ORIENTATION : N

CONTACT TYPE : PIN(500 Matings)

CONTACT LAYOUT : 25-37

Contact Layout



| Contacts (Insert arrangement 25-37) | | | | | |
|--|--------------|--------------|---------------------|-------------|-------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +000 (0.00) | +472 (11.99) | W | +242 (6.15) | +236 (5.99) |
| B | +185 (4.70) | +472 (11.99) | X | +326 (8.28) | +086 (2.18) |
| C | +333 (8.46) | +382 (9.70) | Y | +326 (8.28) | -086 (2.18) |
| D | +441 (11.20) | +249 (6.32) | Z | +242 (6.15) | -236 (5.99) |
| E | +500 (12.70) | +086 (2.18) | a | +086 (2.18) | -320 (8.13) |
| F | +500 (12.70) | -086 (2.18) | b | -086 (2.18) | -320 (8.13) |
| G | +441 (11.20) | -249 (6.32) | c | -242 (6.15) | -236 (5.99) |
| H | +333 (8.46) | +382 (9.70) | d | -326 (8.28) | -086 (2.18) |
| J | +186 (4.72) | -472 (11.99) | e | -326 (8.28) | +086 (2.18) |
| K | +000 (0.00) | -472 (11.99) | f | -242 (6.15) | +236 (5.99) |
| L | -186 (4.72) | -472 (11.99) | g | -086 (2.18) | +320 (8.13) |
| M | -333 (8.46) | -382 (9.70) | h | +000 (0.00) | +172 (4.37) |
| N | -441 (11.20) | -249 (6.32) | k | +154 (3.91) | +086 (2.18) |
| P | -500 (12.70) | -086 (2.18) | m | +154 (3.91) | -086 (2.18) |
| R | -500 (12.70) | +086 (2.18) | n | +000 (0.00) | -172 (4.37) |
| S | -441 (11.20) | +249 (6.32) | p | -154 (3.91) | -086 (2.18) |
| T | -333 (8.46) | +382 (9.70) | q | -154 (3.91) | +086 (2.18) |
| U | -186 (4.72) | +472 (11.99) | r | +000 (0.00) | +000 (0.00) |
| V | +086 (2.18) | +320 (8.13) | --- | --- | --- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 25 | 37 | 37 | 16 | II | All | --- |

Panel Cutout



| Dim | Nominal |
|-----|------------|
| ØA | 42.47 min |
| ØAA | 37.69 min |
| R1 | 38.1 |
| ØT | 3.81 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D025Z37PN

| | | | |
|----------------|---------------------------------------|----------------------------|---|
| A | 10-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D025Z37PN-C | | SHEET 2/2 |