USB 3.1 Gen 1 USB-C Portable Hub with 4 USB-A Ports and USB-C PD Charging Port, Thunderbolt 3 Compatible

MODEL NUMBER: **U460-004-4A-C**

Adds USB-A and USB-C PD charging ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

Description

The U460-004-4A-C USB 3.1 Gen 1 USB-C Portable Hub expands the potential of your tablet, laptop, MacBook, Chromebook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for adding a thumb drive and other USB peripherals and powering and charging a PD Charging-compliant mobile device—all at the same time.

The plug-and-play U460-004-4A-C requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Four USB-A ports accept USB peripherals, such as a flash drive, mouse, keyboard or printer, and the dedicated BC 1.2-compliant one provides up to 1.5A for charging smartphones and other mobile devices. All ports support fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.

The USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook or Chromebook) connected to the U460-004-4A-C. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W).

Features

Turn Your Device's USB-C Port into a Multiport Workstation Ideal for adding USB peripherals and powering and charging a PD Charging-compliant mobile device simultaneouslyPlug-and-play operation with no software, drivers or external power requiredAbout the size of a credit card for easy carrying in a pocket, purse or laptop bag
Connect USB Peripherals4 USB-A ports accept flash drives, mice, keyboards, printers and other USB peripheralsBC 1.2-compliant USB-A port provides up to 1.5A for charging mobile devicesSupports USB 3.1 Gen 1 data transfer rates up to 5 GbpsBackward compatible with USB 2.0 and USB 1.1
Charge a Connected DeviceUSB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 deviceSupports power input up to 20V 3A (60W)
Built-In Cable with Reversible USB-C Connector Fumble-free reversible USB-C plug connects in either

Highlights

- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- USB-C PD charging port supports power input up to 20V 3A (60W)
- BC 1.2-compliant USB-A port provides up to 1.5A for charging devices
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required

System Requirements

- Source device with USB-C or Thunderbolt 3 port

Package Includes

- U460-004-4A-C USB 3.1 Gen 1 USB-C Portable Hub
- Owner's manual

direction for quick connection every time

Specifications

OVERVIEW	
UPC Code	037332193773

OUTPUT	
Charging Ports / Amps	0.9A; 1.5A; 3A
Charging Watts	60

INPUT	
Bus Powered	Yes
Product Length (in.)	6
Product Length (cm.)	15.24
Product Length (ft.)	0.5
Product Length (m.)	0.15

BATTERY	
Battery Charging (1.2 Port)	Yes

PHYSICAL	
Shipping Dimensions (hwd / in.)	0.90 x 3.90 x 5.60
Shipping Weight (lbs.)	0.20
Unit Packaging Type	Box
Unit Dimensions (hwd / in.)	0.43 x 3.7 x 1.6
Unit Weight (lbs.)	0.1
Unit Weight (kg)	0.05
Material of Construction	ABS, PVC
Color	White
Cable Jacket Rating	VW-1

ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 158 F (-10 to 70 C)
Relative Humidity	10% to 90% RH, Non-Condensing
BTUs	7.5 BTU/Hr

Power Consumption (Watts)	2.2
Power Provided to Connected Device(s)	Up to 20V 3A (60W) Input (USB-C), 5V 1.5A (7.5W) Output BC 1.2 USB port, 5V 0.9A (4.5W) Output per USB port

CONNECTIONS	
Ports	5
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	(4) USB 3.0 A (FEMALE)
Side B - Connector 2	USB C (FEMALE)
Connector Plating	Nickel

FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
UASP Support	No
USB Power Delivery (PD) Charging Support	Yes
Technology	USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1)

CERTIFICATIONS	
Certifications	Tested to CE, FCC, RoHS, REACH

WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty