



Mallory Sonalert Products, Inc.

Part #: **ZA028SDMT2**

Sales Outline Drawing

Revision: **F**

Specifications:

| | | | | |
|------------------------|---|--|--|---|
| Sound Level Category: | Soft | Soft | Soft | Soft |
| Mode of Operation: | Continuous | Slow Pulse @ 1 PPS | Fast Pulse @ 10 PPS | Chime @ Once per 3 Seconds |
| Loudness @ 2 FT: | 65 to 75 dB(A) Typ. | 65 to 75 dB(A) Typ. | 65 to 75 dB(A) Typ. | 65 to 75 dB(A) Typ. |
| Frequency: | 3900 ± 500 Hz | 3900 ± 500 Hz | 3900 ± 500 Hz | 3700 ± 500 Hz |
| Connection: | "+" to Positive, "-" to Ground | "+" to Positive, "-" and "1" to Ground | "+" to Positive, "-" and "2" to Ground | "+" to Positive, "-", "1" and "2" to Ground |
| Voltage Rating: | 16 to 28 VDC | | | |
| Current Draw: | 40mA MAX | | | |
| Housing Material: | 6/6 Nylon, Color: Black | | | |
| Storage Temperature: | -40° to +80° C | | | |
| Operating Temperature: | -30° to +65° C | | | |
| Panel Mounting: | Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole. | | | |
| Knurled Nut: | Used to attach part to panel. The max recommended torque is 10 in-lbs. | | | |
| Weight (Typical): | 28 g | | | |
| NEMA 3R, 4X, & 12: | Approved with use of included gasket. | | | |
| cUL Recognition: | cUL Recognized | | | |
| Options: | Please contact factory. | | | |

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

PATENT NUMBER 9576442

