TOLERANCE
 THIS IS A C.A.D. GENERATED DRAWING


 UNLESS OTHERWISE SPECIFIED
 DO NOT MAKE MANUAL REVISIONS TO MASTER.


 .X
 ±0.25



	ISSUE NUMBER
1	ORIGINAL

(1)





NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

OPERATING TEMPERATURE:

.XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING: 10A (CURRENT)

-55°C ~ 125°C

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: 10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 10A (CURRENT) IG: 5A PER CONTACT 10mΩ MAX.


STEEL, NICKEL PLATED

THERMOPLASTIC POLYESTER, UL94V-0


COPPER ALLOY, 30µ" GOLD PLATED

5000MΩ min.

1000V AC rms



ſ			SW REFERENCE NO.: 629 COMBO ASSEMBLY		
	COMBINATION	DRAWN: C.B	DATE: JAN. 01/201	19	
1			CHECKED:	DATE:	
ļ	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
YOUR CONNECTION	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-3WK	3640-1N6	ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 629-3WK	3640-1N6	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

