

MMK5225K63J06L4BULK

Aliases (F601JU225K063C)

Not for New Design • Recommended Replacement Series R60

MMK/F601, Film, Metallized Polyester, General Purpose, 2.2 uF, 10%, 63 VDC, 85°C, Lead Spacing = 5mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|--------------|
| L | 7.2mm MAX |
| H | 13mm MAX |
| T | 7.2mm MAX |
| S | 5mm +/-0.4mm |
| LL | 5mm NOM |
| F | 0.5mm NOM |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 1000 |

General Information

| | |
|------------------|--|
| Series | MMK/F601 |
| Dielectric | Metallized Polyester |
| Style | Radial |
| Features | DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 1.412 g |
| Notes | Not for new design - the replacement series is: R60. |

Specifications

| | |
|-----------------------|-------------------------|
| Capacitance | 2.2 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 40 VAC |
| Voltage DC | 63 VDC, 48.8 VDC (100C) |
| Temperature Range | -55/+100°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.8% 1kHz, 1.5% 10kHz |
| Insulation Resistance | 2.2727 GOhms |
| Max dV/dt | 25 V/us |
| Inductance | 6 nH |