


THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.




.XX ±0.13


.XXX ±0.05

N	0	ΓE	S	

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	75Ω (IMPEDANCE)	\geq
SIGNAL CONTACT CURRENT RATING:		-
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	1
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC		`
WITHSTANDING VOLTAGE:	1000V AC rms	



			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINA	COMBINATION D-SUB			19		
			DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
		DRAWING NUMBER: 630-3W3-640-7TC		ISSUE		
YOUR CONNECTION TO QUALITY & SERV	CE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 630-3W3	-640-7TC	1		



HS

COMPLIANT

П

