Image: control of the state state of th		T G	П	m	D	0	B		
Contraction Cont	4		ØF						4
CHARACTERSTICS Studied: Based on MIL DTL 38999 Series III Shell Material Aurminian Shell Material Material Self Kort Dissumer Material Generator Material Material Self Kort Dissonal Material Ourse of the folde Over Copper Alloy 0.8µm minimum Material Ourse of the folde Over Copper Alloy 0.8µm minimum Material Ourse of the folde Over Copper Alloy 0.8µm minimum Material Ourse of the folde Over Copper Alloy 0.8µm minimum Material Ourse of the folde Over Copper Alloy 0.8µm minimum Material Sold Store 9 Material Material <	ω					LAYOUT SHOWN AS EXAM	PLE		3
Sundard : Based on MIL DTL-38999 Series III Image: Control Using and the conternatis the control Using and the control Using and t			Keying Shown as e	example					
Shell Material : Autminum - Shell Material : Autminum 2 31.5 Max SoulRAU shall not be liable for any nan-conformity or damage due to a use of the Poducts which does not comply with it the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specifications issue of the Poducts which does not comply with the Specification is the poly of the Parties of the P			E	Connector dimension Dim Nominal					
Image: Solution in the property of Sourial contact Solution is the property of Sourial is the property of Sour		-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic		Z 31.5 Max		due to a use of the Products which on the Specifications issued by either of the	loes not comply with Parties or by a third party		
-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Sait Spray : 500 hours A 27-09-2016 First Release ISS DATE Latest modification - by MOD N* Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series SCALE General linear NPRDS / PROJECT Tolerances: 859 1 1 13 Z 08 B CONTACT TYPE : Standard Crimp Contact SHELL SZE : 13 PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(S00 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(S00 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(S00 Matings) CONTACT TYPE : SOCK	N								2
-Salt Spray : 500 hours -Salt Spray : 500 hours A 27-09-2016 First Release MOD N° ISS DATE Latest modification - by MOD N° BASIC SERIES: 8D 1 13 Z 08 B B SHELL TYPE Is line Receptacle ORIENTATION : B SCALE General linear NPRDS / PROJECT Tolerances: 859 1 1 CONTACT TYPE Standard Crimp Contact ORIENTATION : B SOURIAU WWW.SOURIAU.COM This document is the property of source or communicated without permission 1 PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) Imast not be reproduced or communicated without permission 1/2						PN: 8D113Z08	3BB		
ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 1 13 Z 08 B B SHELL TYPE : In line Receptacle ORIENTATION : B SCALE General linear NPRDS / PROJECT 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : B SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU SOURIAU SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET VA SOURIAU DRG N° SHEET 1/2					A 27-09-20	016 First Release		·	
BASIC SERIES: 8D 1 - 13 Z 08 B B SCALE General linear NPRDS / PROJECT 859 1 - 13 Z 08 B B ORIENTATION :: B NA General linear NPRDS / PROJECT 859 1 - 13 Z 08 B B ORIENTATION :: B NA Contact TYPE :: Standard Crimp Contact SURIAU This document is the property of SURIAU SURIAU This document is the property of communicated without permission SURIAU This document is the property of SURIAU SURIAU This document is the property of communicated without permission PLATING : Z Black Zinc Nickel CONTACT TYPE : SOCKET (500 Matings) CONTACT LAYOUT : 13-08 FORMAT SOURIAU DRG N° SHEET A3 8D113Z08BB-C 1/2							CUSTOMER DRAWING	MOD N°	
BASIC SERIES. OB I					TITLE	Aluminium In	line plug 8D series		
SHELL TYPE : in line Receptacle ORIENTATION : B ORIENTATION : B SOURIAU This document is the property of SOURIAU.COM SHELL SIZE : 13 CONTACT TYPE : Standard Crimp Contact CONTACT TYPE : SOCKET(500 Matings) SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET (500 Matings) FORMAT SOURIAU DRG N° SHEET A3 8D113Z08BB-C 1/2			08 B B						
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 13-08 FORMAT SOURIAU DRG N° SHEET A3 8D113Z08BB-C 1/2		CONTACT TYPE : Standard Crimp Contact		SOURIA	SOURIAU Early WWW.SOURIAU.COM This document is the property SOURIAU it must not be reproduced o				
					3-08 FORMAT		RG N°	SHEET	
$\mathbf{M} = \mathbf{M} = $	L	H G	F	Ε		8D113208I	B A	1/2	l

	т	۵	П	п	D	0	σ	A		-
		Contact Layout								
4		$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & & \\ & $								4
		Contacts (Insert arrangement 13-8) Contact position ID Contact location (mm) A +.065 (1.65) +.157 (3.99) B +.170 (4.32) +.000 (0.00) C +.120 (3.05) 120 (3.05) D ·.000 (0.00) 170 (4.32) E 120 (3.05) 120 (3.05) F 170 (4.32) +.000 (0.00) G 065 (1.65) +.157 (3.99) H +.000 (0.00) +.044 (1.12)								
ω	Shell Arrangement size no. 13 -8	Number of contacts Size contacts Service rating Contact location Supersedes 8 20 I All MS20051-8								3
						SOURIAU shall not be liab				
						the Specifications issued by	ducts which does not con either of the Parties or by nmendation, technical no	y a third party		
N								ction & Control List Not Listed		2
						PN: 8D113Z08BB				
_					ISS DATE	First Release			MOD N°	
			Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series						_	
					SCALE -	$\nabla (\nabla \Psi)$	Il linear ances:	NPRDS / PROJECT 859		1
					SOURIAU	· · · · · · · · · · · · · · · · · · ·		This document is the prope SOURIAU it must not be reproduce communicated without per	ed or	
					FORMAT A3		RIAU DRG N° L13Z08BB-C		SHEET 2/2	-
L	Н	G	F	E	D	С	В	A		