


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00550	Connector, 4.75x10.2mm SAE, brass nickel plated, molding type	1	
2	50-00555	Connector, 50 mm, alligator clip, red sleeve	1	
3	50-00556	Connector, 50 mm, alligator clip, black sleeve	1	
4	30-00792	Wire, 2C TS, 16 AWG, UL2651, 300V, 105C, 4.8 mm, VW-1, PVC, red and black	1	
5	24-00176	Overmold, SAE connector, PVC, black	1	black, 105 °C
6	55-00059	Dust cap, SAE connector, overmold fit	1	black, 105 °C



Notes:
Functionally equivalent components may be substituted

Wiring Diagram		
50-00550	wire color	Alligator Clip
pin	red (+)	red
sleeve	black (-)	black

Revision:	Date:	Description:	Prepared: PS <small>Digitally signed by PS Date: 2017.08.11 12:33:50-07'00'</small>	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	1/16/2017	Initial release	Verified: GL <small>Digitally signed by GL Date: 2017.08.11 14:17:36-07'00'</small>	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 305 mm, 50-00550 SAE to alligator clips, 16 AWG, UL2651, 30-00792, R-B wire, cap
					Size: A Part number: 10-02414
					Scale: 1:1
					Sheet 1 of 1