


THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT





| Ν | О. | TE | ES | 1 |
|---|----|----|----|---|
| | | | | |

| MATERIAL: | |
|-----------|--|
| HOUSING: | |
| SHELL: | |
| CONTACT: | |
| | |

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING: 10A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC

WITHSTANDING VOLTAGE:



| | COMBINATION D-SUB | | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | |
|--|--------------------------------------|---|---------------------------|--------------------------------------|------------------|-------|--|
| | | | | C.B | DATE: JAN. 01/20 | 19 | |
| | | | | | DATE: | | |
| | EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND | SCALE: | (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | TORONTO, ONTARIO CANADA | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 630-3W3-6 | | 650-1T1 | ISSUE | |
| | YOUR CONNECTION TO QUALITY & SERVICE | | PART NUM | IBER: 630-3W3- | 650-1T1 | 1 | |

-55°C ~ 125°C

1000V AC rms

