

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.










NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

STEEL, TIN PLATED

THERMOPLASTIC POLYESTER, UL94V-0 COPPER ALLOY, GOLD FLASH PLATED



POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:

.X ±0.25 .XX ±0.13 .XXX ±0.05

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

**OPERATING TEMPERATURE:** 


30A (CURRENT)

-55°C ~ 125°C

 $10m\Omega$  MAX.

5000MΩ min.

1000V AC rms



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY				
CO				DRAWN: C.B		DATE: JAN. 01/2019		
			CHECKED:		DATE:			
	EDAC INC TORONTO, ONTARIO CANADA 9 QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (I	IN C.A.D. 1:1)	SHEET 1	OF	2	
			DRAWING N	NUMBER: 629-3W3	-250-3T5		ISSUE	
YOUR CONNECTION TO QUALI			PART NUME	BER: 629-3W3-	-250-3T5		1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

