

Short Riser Panels for Hot/Cold Aisle Containment System - Wide 750 mm Racks, Set of 2

MODEL NUMBER: SRCTMTR750SH



Aisle Containment System keeps hot and cool air separated for better temperature control and equipment performance in hot aisle/cold aisle configurations.

Features

Riser Panels Designed for Extra-Wide 750 mm Server Racks These SmartRack® riser panels attach to the underside of the Tripp Lite aisle containment system's upper support beams. This is to fill the gap between the telescopic beams (SRCTMTLBM, sold separately) and your rack cabinets. All necessary installation hardware is included. The 3U SRCTMTR750SH measures 750 millimeters (30 inches) wide and 133 millimeters (5.2 inches) high to fit 45U standard-width rack enclosures.

Tripp Lite's Aisle Containment System Manages Airflow for More Cooling Efficiency Upon installation in your data center or server room, the modular, easy-to-assemble Aisle Containment System contains the air in a hot aisle or cold aisle, essentially creating a room within the aisle, while still keeping the aisle accessible. No costly contractor or HVAC specialist is required to install the system, which can be expanded or adapted to meet your needs. Assorted frame kits, beam kits, sliding double-door kits, roof panel kits and adapter riser panel kits (all sold separately) are necessary to assemble a hot or cold Aisle Containment System that accommodates the dimensions of your aisle and the rack enclosures within it.

Specifications

OVERVIEW	
UPC Code	037332214355
Accessory Type	Cooling Accessories
Aisle Containment System Component Type	Riser Panel
PHYSICAL	
Color	Black

Highlights

- Riser panels designed for extra-wide 750 mm rack enclosures
- Fill gap between rack cabinets and aisle containment system's telescopic beams
- Minor assembly required using the included hardware

Applications

- Provide a semi-airtight seal to prevent hot and cold air from mixing within a contained aisle in your data center or server room

System Requirements

- SRCTMTLBM Beam Kit
- SRCTMTFRM Frame End Kit
- SRCTMTSDD Sliding Double-Door Kit
- SRCTMTCVR750 Static Roof Panel Kit

Package Includes

- (2) Riser panels
- (2) M6 x 16 screws
- (2) M6 hex nuts
- (4) M6 x 12 self-tapping screws
- (6) M6 washers
- Installation guide

Shipping Dimensions (hwd / in.)	8.27 x 34.53 x 5.71
Shipping Weight (kg)	3.90
Rack Compatibility	750 mm (Wide)
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	5-year limited warranty