TOLERANCE
UNLESS OTHERWISE SPECIFIED

.X	±0.25
.XX	±0.13
.XXX	±0.05

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.

67.00
61.00
52.80
15.30
11.15
10°

6.10
11.00

11.94
13.20

NOTES:

MATERIAL:
HOUSING: THERMOPLASTIC POLYESTER, UL94V-0
SHELL: STEEL, TIN PLATED
CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 40A (CURRENT)
(IF PRESENT)
SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT
SIGNAL CONTACT RESISTANCE: 10mΩ MAX.

INSULATOR RESISTANCE: 5000MΩ min.
DIELECTRIC
 WITHSTANDING VOLTAGE: 1000V AC rms

COMBINATION D-SUB

EDAC INC
TORONTO, ONTARIO
CANADA
YOUR CONNECTION TO QUALITY & SERVICE

SW REFERENCE NO.:   629 COMBO ASSEMBLY

DRAWN: C.B   DATE: JAN. 01/2019

CHECKED: DATE:

SCALE: (IN C.A.D. 1:1)   SHEET   1   OF   2

DRAWING NUMBER: 629-47W1240-4T3   ISSUE

PART NUMBER: 629-47W1240-4T3   1

THIS IS A C.A.D. GENERATED DRAWING
DO NOT MAKE MANUAL REVISIONS TO MASTER.

TOLERANCE UNLESS OTHERWISE SPECIFIED	
.X	±0.25
.XX	±0.13
.XXX	±0.05

2W2

2WK2

5W1

3W3

3WK3

7W2

11W1

9W4

13W3

5W5

17W2

21W1

13W6

17W5

8W8

25W3

27W2

21W4

24W7

36W4

43W2

47W1

COMBINATION D-SUB

SW REFERENCE NO.:	629 COMBO ASSEMBLY
DRAWN: C.B	DATE: JAN. 01/2019
CHECKED:	DATE:
SCALE: N.T.S	SHEET 2 OF 2
DRAWING NUMBER: 629-47W1240-4T3	ISSUE
PART NUMBER: 629-47W1240-4T3	1

EDAC INC
TORONTO, ONTARIO
CANADA
YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.