

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	03JUL2015	DL	CW
	B	ECR-20-014876	27JUL2021	WQR	CW

4X M3 THREAD
4X M3 螺纹孔

PG/M

NOTES:



1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, GRAY
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 灰色
 防护等级: IP65(配合)

4-Ø5.5

T1660244129-000	H24B-SGRH-BO-PG29	H24B HOUSING, SURFACE MOUNTED, 4 EAR, PG29, HIGH CONSTRUCTION, POWDER COATED, GREY H24B下壳, 表面安装, 4耳, PG29, 高结构, 灰色粉末喷涂	PG29
PART NUMBER 零件料号	PART DESCRIPTION 零件描述		PG/M

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 03JUL2015 DAVID LI	 TE Connectivity		
DIMENSIONS: mm		CHK 03JUL2015 CHRIS WANG			NAME H24B-SGRH-BO-PG29
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 03JUL2015 XU XIANG			PRODUCT SPEC 108-137013
		3 PLC ±-	APPLICATION SPEC 114-137013	SIZE A3	
MATERIAL TBD		4 PLC ±-	WEIGHT -	CAGE CODE -	
FINISH -		ANGLES ±-	CUSTOMER DRAWING	DRAWING NO C-T1660244129000	
			SCALE 1:2	RESTRICTED TO	
			SHEET 1 OF 1	REV B	

1470-19 (3/13)