

## Coaxial Cable Connector 11\_1023-C50-2-3/111\_N

### Description

Straight cable plug

Interface standards  
DIN 41626/2



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 4 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0024 kg

#### Environmental Data

Operating temperature -55 °C to 125 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

| Piece Parts    | Material               | Surface Plating                            |
|----------------|------------------------|--|
| Centre contact | Brass                  | Gold Plating (Nickel underplated)          |
| Outer contact  | Copper Beryllium Alloy | Gold Plating (Nickel underplated)          |
| Body           | Brass                  | Gold Plating (Nickel underplated)          |
| Insulator      | PFA / PTFE             |  |
| Crimp ferrule  | Copper                 | Gold Plating (without Nickel underplating) |

### Related Documents

Outline drawing DOU-00006692  
Catalogue drawing DOU-00006694  
Assembly instruction DOC-0000179140

### Ordering Information

Single package 11\_1023-C50-2-3/111\_NE  
Bulk 100 pcs package 11\_1023-C50-2-3/111\_NH

### Additional Information

Suitable cables RG\_316\_/U, ENVIROFLEX\_316, RG\_188\_A/U, RG\_174\_/U