



Product: <u>5501GE</u> ☑

Security & Sound, #22-2c, BC, Shielded, CMR

Product Description

Security & Sound Cable, Riser-CMR, 1-22 AWG stranded bare copper pair with PVC insulation and Beldfoil® shield, 1-22 AWG stranded bare copper conductors with insulation, overall PVC jacket with ripcord

Technical Specifications

Product Overview Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment **Physical Characteristics (Overall)** Conductor AWG Stranding Material No. of Conductors No. of Pairs 22 7x30 BC - Bare Copper 1 1 Conductor Count: 3 Insulation Material Nominal Wall Thickness PVC - Polyvinyl Chloride 0.01 in Color Chart Color Black & Red (shielded pair) White Inner Shield Material Trade Name Coverage [%] Drainwire Material Туре Material **Drainwire AWG** Tape Bi-Laminate (Alum+Poly) Beldfoil® 100% TC - Tinned Copper 24 **Outer Shield** Material No Shield Outer Jacket **Nominal Diameter** Nominal Wall Thickness Materia PVC - Polyvinyl Chloride 0.171 in 0.015 in **Electrical Characteristics** Conductor DCR Nominal Conductor DCR 16.4 Ohm/1000ft Capacitance Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Other Conductor to Shield 46 pF/ft 82.8 pF/ft

Inductance

Nominal Inductance

0.18 µH/ft

Current

Max. Recommended Current [A] 2.8 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

Operating Temperature Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	15.1 lbs/1000ft
Max. Pull Tension:	32.8 lbs
Min. Bend Radius/Minor Axis:	1.8 in

Standards

NEC/(UL) Compliance:	CMR
CEC/C(UL) Compliance:	CMG

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2003/96/EC (BFR):	Yes	
EU Directive 2011/65/EU (RoHS 2):	Yes	
EU Directive 2012/19/EU (WEEE):	Yes	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes	
MII Order #39 (China RoHS):	Yes	

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number: 6	6501GE

Related Part Numbers

Variants

Item #	Color	UPC
5501GE 008U1000	Gray	612825163213

History

Update and Revision: Revision Number: 0.312 Revision Date: 05-05-2023

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.