


LDBAA2390GC5N0

Aliases (DBAA2390GC5N0)

LDB, Film, Metallized PPS Stacked, General Purpose, 0.039 uF, 2%, 16 VDC, 125°C, 1206, 1.2mm



| General Information | |
|---------------------|------------------------|
| Series | LDB |
| Dielectric | Metallized PPS Stacked |
| Style | SMD Chip |
| RoHS | Yes |
| AEC-Q200 | No |
| Component Weight | 0.06 g |
| Shelf Life | 104 Weeks |
| MSL | 3 |

| Specifications | |
|-----------------------|------------|
| Capacitance | 0.039 uF |
| Capacitance Tolerance | 2% |
| Voltage DC | 16 VDC |
| Temperature Range | -55/+125°C |
| Rated Temperature | 125°C |
| Dissipation Factor | 0.6% 1kHz |
| Insulation Resistance | 3 GOhms |

Click here for the 3D model.

| Dimensions | |
|------------|-------------------|
| Chip Size | 1206 |
| L | 3.3mm +0.3/-0.1mm |
| W | 1.7mm +/-0.2mm |
| Т | 1.2mm MAX |
| В | 0.4mm +0.5/-0.3mm |

Packaging Specifications

| Packaging | T&R |
|--------------------|------|
| Packaging Quantity | 3000 |
| Fackaging Quantity | 3000 |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.