

SIDE VIEW



TERMINAL END VIEW



Click [here](#) for the 3D model.

| Dimensions | |
|-------------|---------------|
| D | 22mm +/-0.5mm |
| L | 40mm +2mm |
| S | 10mm +/-0.5mm |
| LL Negative | 15mm MIN |
| LL Positive | 20mm MIN |
| F | 0.8mm NOM |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 300 |

General Information

| | |
|-------------|--|
| Series | ESG |
| Dielectric | Aluminum Electrolytic |
| Description | Long Life Single Ended Aluminum Electrolytic |
| Features | Long Life |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |

Specifications

| | |
|-------------------------|--------------------------|
| Capacitance | 150 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 400 VDC, 450 VDC (Surge) |
| Temperature Range | -40/+105°C |
| Rated Temperature | 105°C |
| Life | 5000 Hrs |
| Dissipation Factor | 24% 120Hz 20C |
| Ripple Current | 650 mAmps (120Hz 105C) |
| Leakage Current | 3610 uA (2min 20°C) |
| Impedance Ratio at -25C | 5 |
| Impedance Ratio at -40C | 6 |