

REV. C
DCO 300853


TOLERANCES ±.010" - UNLESS OTHERWISE SPECIFIED

| | |
|-----------------|-----------------------------|
| COIL: @ 25°C | |
| RESISTANCE | 70 OHMS ±10% |
| NOMINAL VOLTAGE | 12 VDC |
| MUST OPERATE | 6.9 VDC MAX. |
| MUST RELEASE | 3.3 VDC MAX., 0.75 VDC MIN. |

| | |
|--------------|---------------------------|
| ENVIRONMENT: | |
| VIBRATION | 33 Hz TO 3000 Hz @ 30 g's |
| SHOCK | 200 g's 6 MS. DURATION |
| TEMPERATURE | -70 °C TO +125 °C |

NOTES: OPERATE, RELEASE 15 MS MAX.
CONTACT BOUNCE 1 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: 25 AMPS 28 VDC, 115 VAC 400 Hz RESISTIVE
50,000 OPERATIONS

DR. B.D. 10APR2008 CK. J.M.B. 5/14/08

Tyco Electronics ©COPYRIGHT 2005
TYCO ELECTRONICS CORPORATION
ALL INTERNATIONAL RIGHTS RESERVED

CUST. CATALOG _____
CUST. NO. _____ REV. N/A

TE NUMBER
4-1617753-5

CII PART NUMBER
FCA-325-BY2