



Click [here](#) for the 3D model.

Dimensions	
D	76mm +/-1mm
L	95mm +/-2mm
L1	101mm +/-2mm
S	31.7mm +/-0.2mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	9

General Information	
Series	C44U
Dielectric	Metallized Polypropylene
Style	Can
Features	Standard Duty
RoHS	With Exemptions
REACH	SVHC (Pb - CAS 7439-92-1)
Lead	Threaded Studs M8
AEC-Q200	No
Miscellaneous	Thermal Resistance = 6.4 C/W. Weight = 610 grams.

Specifications	
Capacitance	270 uF
Capacitance Tolerance	10%
Voltage DC	900 VDC
Temperature Range	-40/+85°C
Rated Temperature	75°C
Insulation Resistance	110 MOhms
Max dV/dt	10 V/us
Resistance	1.8 mOhms (10kHz)
Ripple Current	50 Amps (10kHz 40C), 2700 Amps (Peak)
Inductance	36 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.