


a YAGEO company

A768MS566M1KLAE034

A768, Polymer Aluminum, 56 uF, 20%, 80 VDC, -55/+125°C



Click here for the 3D model.

Dimensions	
D	10mm +/-0.5mm
L	12.2mm +/-0.5mm
W	10.3mm +/-0.2mm
Н	10.3mm +/-0.2mm
С	11mm +/-0.2mm
Р	4.6mm NOM
R	0.8 - 1.1mm

Packaging Specifications		
Packaging	T&R, 380mm	
Packaging Quantity	400	

General Information		
Series	A768	
Dielectric	Polymer Aluminum	
Style	SMD Can	
Description	Surface Mount, Polymer Aluminum	
RoHS	Yes	
Lead	V-Chip	
AEC-Q200	No	
Halogen Free	Yes	

Specifications			
56 uF			
20%			
80 VDC, 92 VDC (Surge)			
-55/+125°C			
125°C			
2000 Hrs			
34 mOhms (100kHz 20C)			
1800 mAmps (100kHz 125C)			
896 uA (2min 20°C)			
Yes			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.