

## ATGBICS CWDM-SFP-2.5G-1370-40-C network transceiver module Fiber optic 2500 Mbit/s 1370 nm

**Brand :** ATGBICS **Product code:** CWDM-SFP-2.5G-1370-40-C

Product name: CWDM-SFP-2.5G-1370-40-C

ATGBICS

Re (f Made AFTERDAMENTAL AND AFTERDAMEN

Cisco Compatible Transceiver, CWDM SFP 2.5G, 40km, SMF, LC, 1370nm

ATGBICS CWDM-SFP-2.5G-1370-40-C network transceiver module Fiber optic 2500 Mbit/s 1370 nm:

ATGBICS CWDM-SFP-2.5G-1370-40 2.5GBase CWDM supports a distance of up to 40km over single mode fibre (SMF) using a wavelength of 1370nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of CiscoCWDM-SFP-2.5G-1370-40= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 2500 Mbit/s  Interface type * SFP  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector LC  SFP transceiver standard CWDM  Maximum transfer distance 40000 m  Wavelength 1370 nm  Coarse Wavelength Division Multiplexing (CWDM)  Ethernet interface type 25 Gigabit Ethernet  Digital Diagnostics Monitoring (DDM)	2500 Mbit/s SFP	Brand compatibility	Cisco
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%	
Features Product colour Housing material	duct colour Silver using material Metal	Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 15 g
Plug and Play  Hot-swap  Easy to install  Country of origin  Vited Ki	<b>√</b>	Packaging data	
	✓ United Kingdom	Number of products included Package type	1 pc(s) Box
		Technical details	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.