

# Monitor - VL FPM 17B - 2404325

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



17"/43 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports.

Similar figure



## Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626460598

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Outer dimensions: width, height, depth	452 mm x 356.5 mm x 50 mm (Includes bezel)
Installation dimensions: width, height, depth	424 mm x 329.5 mm (Panel cutout)

### Display

Display	43,2 cm / 17"-TFT
Screen resolution	1280 x 1024 Pixel(s) (SXGA)
Touch technology	analog resistive (polyester)
Brightness	350 cd/m <sup>2</sup> , typical (adjustable)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Colors	16.7 million colors

### Monitor data

Network	Without network
Interfaces	1x USB 1.1, Typ A

# Monitor - VL FPM 17B - 2404325

## Technical data

### Monitor data

	1x USB 2.0, Typ A
Monitor output	1x DVI-D
	1x VGA
Slots	without slots

### General

Note	Order information: This VL FPM does not include the Phoenix Contact logo on the front panel.
Mounting type	VESA MIS-D, 100/75, C
	Front installation
Weight	6.43 kg

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

### Device supply

Supply voltage	24 V DC (typical)
Supply voltage range	19.2 V DC ... 28.8 V DC
Power supply unit	24 V DC ±20 %

### Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

### Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>