

R71MF3220DQ30M

Aliases (71MF3220DQ30M)

R71, Film, Metallized Polypropylene, General Purpose, 0.22 uF, 20%, 420 VDC, 105°C, Lead Spacing = 10mm



Click [here](#) for the 3D model.

Dimensions

L	13mm +0.2/-0.5mm
H	12mm +0.1/-0.5mm
T	6mm +0.2/-0.5mm
S	10mm +/-0.4mm
H0	18.5mm +/-0.5mm
F	0.6mm +/-0.05mm

Packaging Specifications

Packaging	Ammo, 360x340x59mm, Box
Packaging Quantity	680

General Information

Series	R71
Dielectric	Metallized Polypropylene
Style	Radial
Features	PFC and Pulse
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No
Component Weight	1.453 g
Miscellaneous	Above 105C DC And AC Voltage Derating Is 4%/C.

Specifications

Capacitance	0.22 uF
Capacitance Tolerance	20%
Voltage AC	220 VAC
Voltage DC	420 VDC
Temperature Range	-40/+110°C
Rated Temperature	105°C
Dissipation Factor	0.1% 25C
Insulation Resistance	100 GOhms
Max dV/dt	250 V/us
Resistance	180.9 mOhms (100kHz)
Ripple Current	0.85 Amps (100kHz 85C), 55 Amps (Peak)
Inductance	9 nH